

compensation agreements. The Employee Retirement Income Security Act of 1974 section 408(a) authorizes this information collection. *See* 29 U.S.C. 1108(a).

This information collection is subject to the PRA. A Federal agency generally cannot conduct or sponsor a collection of information, and the public is generally not required to respond to an information collection, unless the OMB under the PRA approves it and displays a currently valid OMB Control Number. In addition, notwithstanding any other provisions of law, no person shall generally be subject to penalty for failing to comply with a collection of information that does not display a valid Control Number. *See* 5 CFR 1320.5(a) and 1320.6. The DOL obtains OMB approval for this information collection under Control Number 1210-0065.

OMB authorization for an ICR cannot be for more than three (3) years without renewal, and the current approval for this collection is scheduled to expire on August 31, 2019. The DOL seeks to extend PRA authorization for this information collection for three (3) more years, without any change to existing requirements. The DOL notes that existing information collection requirements submitted to the OMB receive a month-to-month extension while they undergo review. For additional substantive information about this ICR, see the related notice published in the **Federal Register** on March 27, 2019 (84 FR 11573).

Interested parties are encouraged to send comments to the OMB, Office of Information and Regulatory Affairs at the address shown in the **ADDRESSES** section within thirty-(30) days of publication of this notice in the **Federal Register**. In order to help ensure appropriate consideration, comments should mention OMB Control Number 1210-0065. The OMB is particularly interested in comments that:

- Evaluate whether the proposed collection of information is necessary for the proper performance of the functions of the agency, including whether the information will have practical utility;
- Evaluate the accuracy of the agency's estimate of the burden of the proposed collection of information, including the validity of the methodology and assumptions used.
- Enhance the quality, utility, and clarity of the information to be collected; and
- Minimize the burden of the collection of information on those who are to respond, including through the use of appropriate automated,

electronic, mechanical, or other technological collection techniques or other forms of information technology, *e.g.*, permitting electronic submission of responses.

Agency: DOL-EBSA.

Title of Collection: Securities Lending by Employee Benefits Plans, Prohibited Transaction Exemption 2006-16.

OMB Control Number: 1210-0065.

Affected Public: Private Sector—Businesses or other for-profits, not-for-profit institutions.

Total Estimated Number of Respondents: 155.

Total Estimated Number of Responses: 1,550.

Total Estimated Annual Time Burden: 297 hours.

Total Estimated Annual Other Costs Burden: \$12,765.

Authority: 44 U.S.C. 3507(a)(1)(D).

Dated: August 14, 2019.

Frederick Licari,

Departmental Clearance Officer.

[FR Doc. 2019-17830 Filed 8-19-19; 8:45 am]

BILLING CODE 4510-29-P

DEPARTMENT OF LABOR

Mine Safety and Health Administration

Petitions for Modification of Application of Existing Mandatory Safety Standards

AGENCY: Mine Safety and Health Administration, Labor.

ACTION: Notice.

SUMMARY: This notice is a summary of petitions for modification submitted to the Mine Safety and Health Administration (MSHA) by the parties listed below.

DATES: All comments on the petitions must be received by MSHA's Office of Standards, Regulations, and Variances on or before September 19, 2019.

ADDRESSES: You may submit your comments, identified by "docket number" on the subject line, by any of the following methods:

1. *Electronic Mail:* zzMSHA-comments@dol.gov. Include the docket number of the petition in the subject line of the message.
2. *Facsimile:* 202-693-9441.
3. *Regular Mail or Hand Delivery:* MSHA, Office of Standards, Regulations, and Variances, 201 12th Street South, Suite 4E401, Arlington, Virginia 22202-5452, Attention: Roslyn B. Fontaine, Deputy Director, Office of Standards, Regulations, and Variances. Persons delivering documents are required to check in at the receptionist's

desk in Suite 4E401. Individuals may inspect copies of the petition and comments during normal business hours at the address listed above.

MSHA will consider only comments postmarked by the U.S. Postal Service or proof of delivery from another delivery service such as UPS or Federal Express on or before the deadline for comments.

FOR FURTHER INFORMATION CONTACT: Roslyn B. Fontaine, Office of Standards, Regulations, and Variances at 202-693-9440 (voice), fontaine.roslyn@dol.gov (email), or 202-693-9441 (facsimile). [These are not toll-free numbers.]

SUPPLEMENTARY INFORMATION: Section 101(c) of the Federal Mine Safety and Health Act of 1977 and Title 30 of the Code of Federal Regulations Part 44 govern the application, processing, and disposition of petitions for modification.

I. Background

Section 101(c) of the Federal Mine Safety and Health Act of 1977 (Mine Act) allows the mine operator or representative of miners to file a petition to modify the application of any mandatory safety standard to a coal or other mine if the Secretary of Labor determines that:

1. An alternative method of achieving the result of such standard exists which will at all times guarantee no less than the same measure of protection afforded the miners of such mine by such standard; or

2. That the application of such standard to such mine will result in a diminution of safety to the miners in such mine.

In addition, the regulations at 30 CFR 44.10 and 44.11 establish the requirements and procedures for filing petitions for modification.

II. Petitions for Modification

Docket Number: M-2019-037-C.

Petitioner: Hampden Coal, LLC, One Oxford Centre, 301 Grant Street, Suite 4300, Pittsburgh, Pennsylvania 15219.

Mines: Buffalo Mine, MSHA I.D. No. 46-09528, located in Logan County, West Virginia.

Regulation Affected: 30 CFR 75.1002(a) (Installation of electric equipment and conductors; permissibility).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, within 150 feet of pillar workings and longwall faces.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372, 75.1002(a), and 75.1200, use of the most practical and accurate surveying equipment is necessary. It is necessary to determine the exact location and extent of mine workings to ensure the safety of miners in active mines and to protect miners in future mines which may mine in close proximity to the active mines.

(2) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater within 150 feet of pillar workings or longwall faces subject to this petition:

—Sokkia CX-105

—TopCon 235

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used within 150 feet of pillar workings or longwall faces will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used within 150 feet of pillar workings or longwall faces will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn further than 150 feet from pillar workings and longwall faces. All requirements of 30 CFR 75.323 will be complied with prior to entering within 150 feet of pillar workings or longwall faces.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of accumulated float coal dust. If the rock-dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and

maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment within 150 feet of pillar workings and longwall faces, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used within 150 feet of pillar workings or longwall faces when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment within 150 feet of pillar workings and longwall faces. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be changed out or charged in fresh air more than 150 feet from pillar workings or longwall faces. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, within 150 feet of pillar workings or longwall faces is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000–23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used within 150 feet of pillar workings or longwall faces, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

- On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.
- Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.
- Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine’s ventilation system that causes the ventilation system not to function in accordance with the mine’s approved ventilation plan.
- If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.
- Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.
- All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.
- The operator will provide annual retraining to all personnel who will be

involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Docket Number: M–2019–038–C.

Petitioner: Hampden Coal, LLC, One Oxford Centre, 301 Grant Street, Suite 4300, Pittsburgh, Pennsylvania 15219.

Mines: Buffalo Mine, MSHA I.D. No. 46–09528, located in Logan County, West Virginia.

Regulation Affected: 30 CFR 75.500(d) (Permissible electric equipment).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, in or in by the last open crosscut.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary.

(2) The operator utilizes the continuous mining method. Accurate surveying is critical to the safety of the miners at the mine.

(3) Mechanical surveying equipment has been obsolete for a number of years. Such equipment of acceptable quality is not commercially available. Further, it is difficult, if not impossible, to have such equipment serviced or repaired.

(4) Electronic surveying equipment is, at a minimum, 8 to 10 times more accurate than mechanical equipment.

(5) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites

and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater in or inby the last open crosscut, subject to this petition:

—Sokkia CX-105

—TopCon 235

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used in or inby the last open crosscut will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used in or inby the last open crosscut will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with

all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn outby the last open crosscut. All requirements of 30 CFR 75.323 will be complied with prior to entering in or inby the last open crosscut.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment within in or inby the last open crosscut, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of accumulated float coal dust. If the rock-dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment in or inby the last open crosscut, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used in or inby the last open crosscut when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment in or inby the last open crosscut. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified person, as defined in 30 CFR 75.151, or be in the process of

being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be charged out or charged in fresh air outby the last open crosscut. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment in or inby the last open crosscut, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, in or inby the last open crosscut is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment in or inby the last open crosscut. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000-23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years

of the date that the petition becomes final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used in or in by the last open crosscut, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

- On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.
- Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.
- Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine’s ventilation system that causes the ventilation system not to function in accordance with the mine’s approved ventilation plan.
- If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all

ventilation controls are reestablished and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.

- Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.
- All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.
- The operator will provide annual retraining to all personnel who will be involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Docket Number: M–2019–039–C.

Petitioner: Hampden Coal, LLC, One Oxford Centre, 301 Grant Street, Suite 4300, Pittsburgh, Pennsylvania 15219.

Mines: Buffalo Mine, MSHA I.D. No. 46–09528, located in Logan County, West Virginia.

Regulation Affected: 30 CFR 75.507–1(a) (Electric equipment other than power-connection points; outby the last open crosscut; return air; permissibility requirements).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use

of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, in return airways.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200(a), use of the most practical and accurate surveying equipment is necessary.

(2) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater in return airways, subject to this petition:

—Sokkia CX–105

—TopCon 235

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used in return airways will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used in return airways will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn out of return airways. All requirements of 30 CFR 75.323 will be complied with prior to entering in return airways.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment in return airways, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of accumulated float coal dust. If the rock-dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment in

return airways, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used in return airways when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment in return airways. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be changed out or charged in fresh air out of return airways. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment in return airways, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, in return airways is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment in return airways.

A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000-23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used in return airways, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

- On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as "baloney skins") or curtains.
- Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.

- Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine's ventilation system that causes the ventilation system not to function in accordance with the mine's approved ventilation plan.
 - If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.
 - Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.
 - All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.
 - The operator will provide annual retraining to all personnel who will be involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.
- The petitioner asserts that the proposed alternative method will at all

times guarantee no less than the same measure of protection afforded by the existing standard.

Docket Number: M–2019–040–C.

Petitioner: Hampden Coal, LLC, One Oxford Centre, 301 Grant Street, Suite 4300, Pittsburgh, Pennsylvania 15219.

Mines: Washington Mine, MSHA I.D. No. 46–09294, located in Logan County, West Virginia.

Regulation Affected: 30 CFR 75.1002(a) (Installation of electric equipment and conductors; permissibility).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, within 150 feet of pillar workings and longwall faces.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372, 75.1002(a), and 75.1200, use of the most practical and accurate surveying equipment is necessary. It is necessary to determine the exact location and extent of mine workings to ensure the safety of miners in active mines and to protect miners in future mines which may mine in close proximity to the active mines.

(2) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater within 150 feet of pillar workings or longwall faces subject to this petition:

—Sokkia CX–105

—TopCon 235

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in

the location where mine record books are kept, or in the location where the surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used within 150 feet of pillar workings or longwall faces will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used within 150 feet of pillar workings or longwall faces will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn further than 150 feet from pillar workings and longwall faces. All requirements of 30 CFR 75.323 will be complied with prior to entering within 150 feet of pillar workings or longwall faces.

(i) Prior to setting up and energizing nonpermissible electronic surveying

equipment within 150 feet of pillar workings or longwall faces, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of accumulated float coal dust. If the rock-dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment within 150 feet of pillar workings and longwall faces, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used within 150 feet of pillar workings or longwall faces when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment within 150 feet of pillar workings and longwall faces. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying

equipment will be changed out or charged in fresh air more than 150 feet from pillar workings or longwall faces. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, within 150 feet of pillar workings or longwall faces is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000-23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be

no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used within 150 feet of pillar workings or longwall faces, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

- On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.
- Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.
- Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine's ventilation system that causes the ventilation system not to function in accordance with the mine's approved ventilation plan.
- If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.
- Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the

surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.

- All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.
- The operator will provide annual retraining to all personnel who will be involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Docket Number: M–2019–041–C.

Petitioner: Hampden Coal, LLC, One Oxford Centre, 301 Grant Street, Suite 4300, Pittsburgh, Pennsylvania 15219.

Mines: Washington Mine, MSHA I.D. No. 46–09294, located in Logan County, West Virginia.

Regulation Affected: 30 CFR 75.500(d) (Permissible electric equipment).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, in or inby the last open crosscut.

The petitioner states that:

- (1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary.
- (2) The operator utilizes the continuous mining method. Accurate

surveying is critical to the safety of the miners at the mine.

(3) Mechanical surveying equipment has been obsolete for a number of years. Such equipment of acceptable quality is not commercially available. Further, it is difficult, if not impossible, to have such equipment serviced or repaired.

(4) Electronic surveying equipment is, at a minimum, 8 to 10 times more accurate than mechanical equipment.

(5) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater in or inby the last open crosscut, subject to this petition:

—Sokkia CX–105

—TopCon 235

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used in or inby the last open crosscut will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

- (i) Checking the instrument for any physical damage and the integrity of the case;
- (ii) Removing the battery and inspecting for corrosion;
- (iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used in or inby the last open crosscut will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn outby the last open crosscut. All requirements of 30 CFR 75.323 will be complied with prior to entering in or inby the last open crosscut.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment within in or inby the last open crosscut, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of accumulated float coal dust. If the rock-dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rocked-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment in or inby the last open crosscut, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used in or inby the last open crosscut when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment in or inby the last open crosscut. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be changed out or charged in fresh air outby the last open crosscut. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment in or inby the last open crosscut, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, in or inby the last open crosscut is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment in or inby the last open crosscut. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000–23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used in or inby the last open crosscut, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

—On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.

—Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.

—Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine's ventilation system that causes the ventilation system not to function in accordance with the mine's approved ventilation plan.

—If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.

—Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.

—All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.

—The operator will provide annual retraining to all personnel who will be involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The

operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Docket Number: M-2019-042-C.

Petitioner: Hampden Coal, LLC, One Oxford Centre, 301 Grant Street, Suite 4300, Pittsburgh, Pennsylvania 15219.

Mines: Washington Mine, MSHA I.D. No. 46-09294, located in Logan County, West Virginia.

Regulation Affected: 30 CFR 75.507-1(a) (Electric equipment other than power-connection points; outby the last open crosscut; return air; permissibility requirements).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, in return airways.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200(a), use of the most practical and accurate surveying equipment is necessary.

(2) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater in return airways, subject to this petition:

—Sokkia CX-105

—TopCon 235

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the

surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used in return airways will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used in return airways will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn out of return airways. All requirements of 30 CFR 75.323 will be complied with prior to entering in return airways.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment in return airways, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of accumulated float coal dust.

If the rock-dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment in return airways, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used in return airways when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment in return airways. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be changed out or charged in fresh air out of return airways. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying

equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment in return airways, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, in return airways is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment in return airways. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000-23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will

apply to all nonpermissible electronic surveying equipment used in return airways, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

—On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.

—Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.

—Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine's ventilation system that causes the ventilation system not to function in accordance with the mine's approved ventilation plan.

—If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.

—Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.

—All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the

date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.

—The operator will provide annual retraining to all personnel who will be involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Docket Number: M-2019-043-C.

Petitioner: Hampden Coal, LLC, One Oxford Centre, 301 Grant Street, Suite 4300, Pittsburgh, Pennsylvania 15219.

Mines: Muddy Bridge Mine, MSHA I.D. No. 46-09514, located in Logan County, West Virginia.

Regulation Affected: 30 CFR 75.1002(a) (Installation of electric equipment and conductors; permissibility).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, within 150 feet of pillar workings and longwall faces.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372, 75.1002(a), and 75.1200, use of the most practical and accurate surveying equipment is necessary. It is necessary to determine the exact location and extent of mine workings to ensure the safety of miners in active mines and to protect miners in future mines which may mine in close proximity to the active mines.

(2) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater within 150 feet of pillar workings or longwall faces subject to this petition:

—Sokkia CX-105

—TopCon 235

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used within 150 feet of pillar workings or longwall faces will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used within 150 feet of pillar workings or longwall faces will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn further than 150 feet from pillar workings and longwall faces. All requirements of 30 CFR 75.323 will be complied with prior to entering within 150 feet of pillar workings or longwall faces.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of accumulated float coal dust. If the rock-dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment within 150 feet of pillar workings and longwall faces, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used within 150 feet of pillar workings or longwall faces when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously

monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment within 150 feet of pillar workings and longwall faces. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be changed out or charged in fresh air more than 150 feet from pillar workings or longwall faces. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, within 150 feet of pillar workings or longwall faces is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition.

When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000–23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used within 150 feet of pillar workings or longwall faces, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

- On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.
- Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.
- Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine’s ventilation system that causes the ventilation system not to function in accordance with the mine’s approved ventilation plan.

—If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.

—Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.

—All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.

—The operator will provide annual retraining to all personnel who will be involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Docket Number: M–2019–044–C.

Petitioner: Hampden Coal, LLC, One Oxford Centre, 301 Grant Street, Suite 4300, Pittsburgh, Pennsylvania 15219.

Mines: Muddy Bridge Mine, MSHA I.D. No. 46–09514, located in Logan County, West Virginia.

Regulation Affected: 30 CFR 75.500(d) (Permissible electric equipment).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, in or inby the last open crosscut.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary.

(2) The operator utilizes the continuous mining method. Accurate surveying is critical to the safety of the miners at the mine.

(3) Mechanical surveying equipment has been obsolete for a number of years. Such equipment of acceptable quality is not commercially available. Further, it is difficult, if not impossible, to have such equipment serviced or repaired.

(4) Electronic surveying equipment is, at a minimum, 8 to 10 times more accurate than mechanical equipment.

(5) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater in or inby the last open crosscut, subject to this petition:

—Sokkia CX–105

—TopCon 235

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the surveying record books are kept. The

logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used in or inby the last open crosscut will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used in or inby the last open crosscut will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn outby the last open crosscut. All requirements of 30 CFR 75.323 will be complied with prior to entering in or inby the last open crosscut.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment within in or inby the last open crosscut, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of

accumulated float coal dust. If the rock-dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment in or inby the last open crosscut, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used in or inby the last open crosscut when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment in or inby the last open crosscut. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be changed out or charged in fresh air outby the last open crosscut. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each

shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment in or inby the last open crosscut, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, in or inby the last open crosscut is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment in or inby the last open crosscut. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000-23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible

electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used in or in by the last open crosscut, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

- On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.
- Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.
- Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine’s ventilation system that causes the ventilation system not to function in accordance with the mine’s approved ventilation plan.
- If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.
- Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.
- All surveyors, section foremen, section crew members, and other personnel who will be involved with

or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.

- The operator will provide annual retraining to all personnel who will be involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Docket Number: M–2019–045–C.

Petitioner: Hampden Coal, LLC, One Oxford Centre, 301 Grant Street, Suite 4300, Pittsburgh, Pennsylvania 15219.

Mines: Muddy Bridge Mine, MSHA I.D. No. 46–09514, located in Logan County, West Virginia.

Regulation Affected: 30 CFR 75.507–1(a) (Electric equipment other than power-connection points; outby the last open crosscut; return air; permissibility requirements).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, in return airways.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200(a), use of the most practical and accurate surveying equipment is necessary.

(2) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater in return airways, subject to this petition:

—Sokkia CX–105

—TopCon 235

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used in return airways will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer’s recommendations. Dates of service will be recorded in the equipment’s logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used in return

airways will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn out of return airways. All requirements of 30 CFR 75.323 will be complied with prior to entering in return airways.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment in return airways, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of accumulated float coal dust. If the rock-dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment in return airways, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used in return airways when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment in return airways. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified

person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be changed out or charged in fresh air out of return airways. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment in return airways, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, in return airways is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment in return airways. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000-23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes

final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used in return airways, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

- On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.
- Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.
- Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine's ventilation system that causes the ventilation system not to function in accordance with the mine's approved ventilation plan.
- If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished

and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.

- Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.
- All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.
- The operator will provide annual retraining to all personnel who will be involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Roslyn B. Fontaine,

Deputy Director, Office of Standards, Regulations, and Variances.

[FR Doc. 2019-17832 Filed 8-19-19; 8:45 am]

BILLING CODE 4520-43-P

DEPARTMENT OF LABOR

Occupational Safety and Health Administration

[Docket No. OSHA-2018-0012]

Advisory Committee on Construction Safety and Health (ACCSH): Notice of Meeting

AGENCY: Occupational Safety and Health Administration (OSHA), Labor.

ACTION: Announcement of a teleconference/WebEx meeting of ACCSH.

SUMMARY: ACCSH will hold a teleconference/WebEx meeting September 9, 2019, to consider a proposed rule on occupational exposure to beryllium and beryllium compounds in the construction industry.

DATES: ACCSH will meet from 10:00 a.m. to 12:00 p.m., ET, Monday, September 9, 2019, by teleconference/WebEx.

ADDRESSES:

Submission of comments and requests to speak: Submit comments and requests to speak at the ACCSH meeting by September 4, 2019, identified by the docket number for this **Federal Register** notice (Docket No. OSHA-2018-0012), using one of the following methods:

Electronically: You may submit comments, including attachments, electronically at: <http://www.regulations.gov>, the Federal eRulemaking Portal. Follow the online instructions for submitting comments.

Facsimile: If your comments, including attachments, do not exceed 10 pages, you may fax them to the OSHA Docket Office at (202) 693-1648.

Regular mail, express mail, hand delivery, and messenger or courier service: You may submit comments and attachments to the OSHA Docket Office, Docket No. OSHA-2018-0012, Occupational Safety and Health Administration, U.S. Department of Labor, Room N-3653, 200 Constitution Avenue NW, Washington, DC 20210. Deliveries (express mail, hand (courier) delivery, and messenger service) are accepted during the OSHA Docket Office's normal business hours, 10:00 a.m. to 3:00 p.m., ET.

Instructions: All submissions must include the agency name and the OSHA docket number for this **Federal Register** notice (Docket No. OSHA-2018-0012). Because of security-related procedures, submissions by regular mail may result in a significant delay in receipt. Please contact the OSHA Docket Office for information about security procedures for making submissions by express mail,

hand (courier) delivery, and messenger service.

Requests for special accommodations: Please submit requests for special accommodations for this ACCSH meeting by September 4, 2019, to Ms. Greta Jameson, OSHA, Office of Communications, Room N-3647, U.S. Department of Labor, 200 Constitution Avenue NW, Washington, DC 20210; telephone: (202) 693-1999; email: jameson.gretah@dol.gov.

FOR FURTHER INFORMATION CONTACT:

For press inquiries: Mr. Frank Meilinger, Director, OSHA Office of Communications, U.S. Department of Labor; telephone (202) 693-1999; email: meilinger.francis2@dol.gov.

For general information about ACCSH: Mr. Damon Bonneau, OSHA, Directorate of Construction, U.S. Department of Labor; telephone (202) 693-2183; email: bonneau.damon@dol.gov.

For copies of this Federal Register Notice: Electronic copies of this **Federal Register** Notice are available at: <http://www.regulations.gov>. This notice, as well as news releases and other relevant information, are also available at OSHA's web page at www.osha.gov.

SUPPLEMENTARY INFORMATION:

I. Background

ACCSH advises the Secretary of Labor and the Assistant Secretary of Labor for Occupational Safety and Health (Assistant Secretary) in the formulation of standards affecting the construction industry, and on policy matters arising in the administration of the safety and health provisions under the Contract Work Hours and Safety Standards Act (Construction Safety Act (CSA)) (40 U.S.C. 3701 *et seq.*) and the Occupational Safety and Health Act of 1970 (OSH Act) (29 U.S.C. 651 *et seq.*) (see also 29 CFR 1911.10 and 1912.3). In addition, the OSH Act and CSA require the Assistant Secretary to consult with ACCSH before the agency proposes any occupational safety and health standard affecting construction activities (29 CFR 1911.10; 40 U.S.C. 3704).

ACCSH operates in accordance with the CSA, the OSH Act, the Federal Advisory Committee Act (FACA) (5 U.S.C. App. 2), and regulations issued pursuant to those statutes (29 CFR part 1912, 41 CFR part 102-3). ACCSH generally meets two times a year.

II. Meeting Information

Attending the meeting: Attendance at this ACCSH meeting will be by teleconference/WebEx only. The dial-in number and passcode for the meeting are as follows: Dial-in number: 1-888-