

Captain of the Port Charleston in the enforcement of the regulated areas.

(c) *Regulations.*

(1) All persons and vessels are prohibited from entering, transiting through, anchoring in, or remaining within the regulated area, except persons and vessels participating in Charleston Race Week or serving as safety vessels. Persons and vessels desiring to enter, transit through, anchor in, or remain within the regulated area may contact the Captain of the Port Charleston by telephone at (843)740-7050, or a designated representative via VHF radio on channel 16, to request authorization. If authorization to enter, transit through, anchor in, or remain within the regulated area is granted by the Captain of the Port Charleston or a designated representative, all persons and vessels receiving such authorization must comply with the instructions of the Captain of the Port Charleston or a designated representative.

(2) The Coast Guard will provide notice of the regulated area by Marine Safety Information Bulletins, Local Notice to Mariners, Broadcast Notice to Mariners, and on-scene designated representatives.

(d) *Enforcement Date.* This rule will be enforced from April 15 through April 17, 2016 from 8:30 a.m. to 5 p.m. daily.

Dated: January 12, 2016.

G. L. Tomasulo,

Captain, U.S. Coast Guard, Captain of the Port Charleston.

[FR Doc. 2016-02280 Filed 2-4-16; 8:45 am]

BILLING CODE 9110-04-P

DEPARTMENT OF TRANSPORTATION

Saint Lawrence Seaway Development Corporation

33 CFR Part 401

[Docket No. SLSDC-2016-0004]

2135-AA39

Seaway Regulations and Rules: Periodic Update, Various Categories

AGENCY: Saint Lawrence Seaway Development Corporation, DOT.

ACTION: Notice of Proposed Rulemaking.

SUMMARY: The Saint Lawrence Seaway Development Corporation (SLSDC) and the St. Lawrence Seaway Management Corporation (SLSMC) of Canada, under international agreement, jointly publish and presently administer the St. Lawrence Seaway Regulations and Rules (Practices and Procedures in Canada) in their respective jurisdictions. Under agreement with the SLSMC, the

SLSDC is amending the joint regulations by updating the Seaway Regulations and Rules in various categories. The changes will update the following sections of the Regulations and Rules: Condition of Vessels; Seaway Navigation; and, Information and Reports. These amendments are necessary to take account of updated procedures and will enhance the safety of transits through the Seaway. Several of the amendments are merely editorial or for clarification of existing requirements.

DATES: Comments are due March 7, 2016.

ADDRESSES: *Docket:* For access to the docket to read background documents or comments received, go to <http://www.Regulations.gov>; or in person at the Docket Management Facility; U.S. Department of Transportation, 1200 New Jersey Avenue SE., West Building Ground Floor, Room W12-140, Washington, DC 20590-001, between 9 a.m. and 5 p.m., Monday through Friday, except Federal Holidays.

FOR FURTHER INFORMATION CONTACT: Carrie Mann Lavigne, Chief Counsel, Saint Lawrence Seaway Development Corporation, 180 Andrews Street, Massena, New York 13662; 315/764-3200.

SUPPLEMENTARY INFORMATION: The Saint Lawrence Seaway Development Corporation (SLSDC) and the St. Lawrence Seaway Management Corporation (SLSMC) of Canada, under international agreement, jointly publish and presently administer the St. Lawrence Seaway Regulations and Rules (Practices and Procedures in Canada) in their respective jurisdictions. Under agreement with the SLSMC, the SLSDC is amending the joint regulations by updating the Regulations and Rules in various categories. The changes will update the following sections of the Regulations and Rules: Condition of Vessels; Seaway Navigation; and, Information and Reports. These updates are necessary to take account of updated procedures which will enhance the safety of transits through the Seaway. Many of these changes are to clarify existing requirements in the regulations. Where new requirements or regulations are made, an explanation for such a change is provided below.

Regulatory Notices: Privacy Act: Anyone is able to search the electronic form of all comments received into any of our dockets by the name of the individual submitting the comment (or signing the comment, if submitted on behalf of an association, business, labor union, etc.). You may review DOT's complete Privacy Act Statement in the

Federal Register published on April 11, 2000 (Volume 65, Number 70; Pages 19477-78) or you may visit <http://www.Regulations.gov>.

The SLSDC is amending four sections of the Condition of Vessels portion of the joint Seaway regulations. In section 401.10, "Mooring lines", the two Corporations are proposing to permit vessels not greater than 200 m in overall length to use soft lines instead of wire lines. Over the past 3 years, vessels greater than 150 m in overall length have been permitted to use type approved soft lines on a test basis, with successful results. Based on these same results, the SLSDC is proposing to amend section 401.11, "Minimum Requirements—mooring lines and fairleads" to permit the operator of vessels of more than 150 m but not more than 200 m to use either soft or wire lines.

In 401.13, "Hand lines", the SLSDC is proposing to change the maximum diameter of hand lines to 18 mm from 17 mm due to the fact that 17 mm lines are no longer available. The proposed change to 401.17, "Pitch indicators and alarms," would make a minor administrative change by removing the effective date for the requirement.

In the Seaway Navigation portion of the regulations, the two Corporations are proposing to make changes in several sections. Section 401.29, "Maximum draft", is being restructured in order to clarify the requirements for use of an operational Draft Information System. In 401.37, "Mooring at tie-up walls", the Seaway Corporations are proposing to require that crew members handling lines on tie-up walls wear approved personal flotation devices instead of life jackets that can be unsafe due to their bulky nature. The SLSDC is proposing to change the requirement in 401.45, "Emergency procedures", to make clear that when a vessel is entering the locks too fast in an emergency situation, the vessel will not be required to deploy mooring lines.

In the Information and Reports section, a change to section 401.79, "Advance notice of arrival, vessels requiring inspection" is being proposed that would require all foreign flagged vessels of 300 GRT or above to submit an electronic Notice of Arrival.

The other changes to the joint regulations are merely editorial or to clarify existing requirements.

Regulatory Evaluation

This proposed regulation involves a foreign affairs function of the United States and therefore Executive Order 12866 does not apply and evaluation under the Department of

Transportation's Regulatory Policies and Procedures is not required.

Regulatory Flexibility Act Determination

I certify that this proposed regulation will not have a significant economic impact on a substantial number of small entities. The St. Lawrence Seaway Regulations and Rules primarily relate to commercial users of the Seaway, the vast majority of who are foreign vessel operators. Therefore, any resulting costs will be borne mostly by foreign vessels.

Environmental Impact

This proposed regulation does not require an environmental impact statement under the National Environmental Policy Act (49 U.S.C. 4321, *et seq.*) because it is not a major federal action significantly affecting the quality of the human environment.

Federalism

The Corporation has analyzed this proposed rule under the principles and criteria in Executive Order 13132, dated August 4, 1999, and have determined that this proposal does not have sufficient federalism implications to warrant a Federalism Assessment.

Unfunded Mandates

The Corporation has analyzed this proposed rule under Title II of the Unfunded Mandates Reform Act of 1995 (Pub. L. 104-4, 109 Stat. 48) and determined that it does not impose unfunded mandates on State, local, and tribal governments and the private sector requiring a written statement of economic and regulatory alternatives.

Paperwork Reduction Act

This proposed regulation has been analyzed under the Paperwork Reduction Act of 1995 and does not contain new or modified information collection requirements subject to the Office of Management and Budget review.

List of Subjects in 33 CFR Part 401

Hazardous materials transportation, Navigation (water), Penalties, Radio, Reporting and recordkeeping requirements, Vessels, Waterways.

Accordingly, the Saint Lawrence Seaway Development Corporation is proposing to amend 33 CFR part 401, Regulations and Rules, as follows:

PART 401—SEAWAY REGULATIONS AND RULES

Subpart A—Regulations

■ 1. The authority citation for subpart A of part 401 continues to read as follows:

Authority: 33 U.S.C. 983(a) and 984(a)(4), as amended; 49 CFR 1.52, unless otherwise noted.

■ 2. In § 401.10, revise paragraph (b) to read as follows:

§ 401.10 Mooring lines.

* * * * *

(b) Unless otherwise permitted by an officer, vessels greater than 200 m shall only use wire mooring lines with a breaking strength that complies with the minimum specifications set out in the table to this section shall be used for securing a vessel in lock chambers.

* * * * *

■ 3. In the table at the end of § 401.10, revise the last sentence of the first column to read as follows:

§ 401.10 Mooring lines.

* * * * *

More than 180 m but not more than 225.5 m * * *

* * * * *

■ 4. In 401.12, revise paragraphs (a)–(d) and add a new paragraph (e) to read as follows:

§ 401.12 Minimum requirements—mooring lines and fairleads.

(a) Unless otherwise permitted by the officer the minimum requirements in respect to mooring lines which shall be available for securing on either side of the vessel, winches and the location of fairleads on vessels are as follows:

(1) Vessels of 100 m or less in overall length shall have at least three mooring lines—wires or synthetic hawsers, two of which shall be independently power operated and one if synthetic, may be hand held;

(i) One line shall lead forward from the break of the bow and one line shall lead astern from the quarter and be independently power operated by winches, capstans or windlasses and lead through closed chocks or fairleads acceptable to the Manager and the Corporation; and

(ii) One synthetic hawser may be hand held or if wire line is used shall be powered. The line shall lead astern from the break of the bow through a closed chock to suitable bits on deck for synthetic line or led from a capstan, winch drums or windlass to an approved fairlead for a wire line.

(2) Vessels of more than 100 m but not more than 150 m in overall length shall have three mooring lines—wires or synthetic hawsers, which shall be independently power operated by winches, capstans or windlasses.

(i) All lines shall be led through closed chocks or fairleads acceptable to the Manager and the Corporation.

(ii) One mooring line shall lead forward and one shall lead astern from the break of the bow and one mooring line shall lead astern from the quarter.

(3) Vessels of more than 150 m but not more than 200 m in overall length shall have four mooring lines, wires or synthetic hawsers, which shall be independently power operated by winches.

(i) One mooring line shall lead forward and one mooring line shall lead astern from the break of the bow.

(ii) One mooring line shall lead forward and one mooring line shall lead astern from the quarter.

(iii) All lines shall be led through a type of fairlead acceptable to the Manager and the Corporation.

(4) Vessels of more than 200 m in overall length shall have four mooring lines—wires, independently power operated by the main drums of adequate power operated winches as follows:

(i) One mooring line shall lead forward and one mooring line shall lead astern from the break of the bow.

(ii) One mooring line shall lead forward and one mooring line shall lead astern from the quarter.

(iii) All lines shall be led through a type of fairlead acceptable to the Manager and the Corporation.

(5) Every vessel shall have a minimum of two spare mooring lines available and ready for immediate use.

* * * * *

■ 5. In § 401.13, revise paragraph (b) to read as follows:

§ 401.13 Handlines.

* * * * *

(b) Be of uniform thickness and have a diameter of not less than 12 mm and not more than 18 mm and a minimum length of 30 m. The ends of the lines shall be back spliced or tapered; and

* * * * *

■ 6. In § 401.17, revise paragraph (b) to read as follows:

§ 401.17 Pitch indicators and alarms.

* * * * *

(b) Visible and audible pitch alarms, with a time delay of not greater than 8 seconds, in the wheelhouse and engineer room to indicate wrong pitch.

■ 7. In § 401.29, revise paragraph (c) as follows:

§ 401.29 Maximum draft.

* * * * *

(c) Any vessel will be permitted to load at an increased draft of not more than 7 cm above the maximum permissible draft in effect as prescribed under § 401.29(b) if it is equipped with a Draft Information System (DIS) and meets the following:

(1) An operational Draft Information System (DIS) approved by a member of the International Association of Classification Societies (IACS) as compliant with the Implementation Specifications found at *www.greatlakes-seaway.com* and having on board:

- (i) An operational AIS with accuracy = 1 (DGPS); and
- (ii) Up-to-date electronic navigational charts; and
- (iii) Up-to-date charts containing high resolution bathymetric data; and

(2) The DIS Tool Display shall be located close to the primary conning position, be visible and legible; and equipped with a pilot plug, if using a portable DIS.

(i) Verification document of the DIS must be kept on board the vessel at all times and made available for inspection.

(ii) A company letter attesting to officer training on use of the DIS must be kept on board and made available for inspection.

(iii) In every navigation season, a vessel intending to use the DIS must notify the Manager of the Corporation in writing at least 24 hours prior to the commencement of its initial transit in the System with the DIS.

(iv) If for any reason the DIS or AIS becomes inoperable, malfunctions or is not used while the vessel is transiting at a draft greater than the maximum permissible draft prescribed under § 401.29(b) in effect at the time, the vessel must notify the Manager or the Corporation immediately.

■ 8. In § 401.37, revise paragraph (b) as follows:

§ 401.37 Mooring at tie-up walls.

* * * * *

(b) Crew members being put ashore on landing booms and handling mooring lines on tie-up walls shall wear approved personal flotation devices.

■ 9. Revise § 401.44 as follows:

§ 401.44 Mooring in locks.

(a) Mooring lines shall only be placed on mooring posts as directed by the officer in charge of the mooring operation.

(b) No winch from which a mooring line runs shall be operated until the officer in charge of a mooring operation has signaled that the line has been placed on a mooring post.

(c) Once the mooring lines are on the mooring posts, lines shall be kept slack until the “all clear” signal is given by the lock personnel. When casting off signal is received, mooring lines shall be kept slack until the “all clear” signal is given by the lock personnel.

(d) Vessels being moored by “Hands Free Mooring” system (HFM) shall have

a minimum of 2 well rested crew members on deck during the lockage.

■ 10. Revise § 401.45 as follows:

§ 401.45 Emergency procedure.

When the speed of a vessel entering a lock chamber has to be checked, the master shall take all necessary precautions to stop the vessel in order to avoid contact with lock structures. At no time shall the vessel deploy its anchors to stop the vessel when entering a lock chamber.

■ 11. Revise § 401.47 as follows:

§ 401.47 Leaving a lock.

(a) Mooring lines shall only be cast off as directed by the officer in charge of a mooring operation.

(b) No vessel shall proceed out of a lock until the exit gates, ship arresters and the bridge, if any, are in a fully open position.

(c) When “Hands Free Mooring system (HFM) is used, no vessel shall use its engine(s) until the lock operator provides the “all clear” instruction.

■ 12. In § 401.79 revise paragraph (a) as follows:

§ 401.79 Advance notice of arrival, vessels requiring inspection.

(a) Advance notice of arrival. All foreign flagged vessels of 300 GRT or above intending to transit the Seaway shall submit a completed electronic Notice of Arrival (NOA) prior to entering at call in point 2 (CIP2) as follows:

* * * * *

■ 13. In § 401.80 add a new paragraph (c) as follows:

§ 401.80 Reporting dangerous cargo.

* * * * *

(c) Vessels carrying “Certain Dangerous Cargo (CDC) as defined in the Transport Canada “Marine Transportation Security Regulations” (MTSR’s) and the United States Coast Guard regulations under the Marine Transportation Security Act shall report the “Certain Dangerous Cargo” to the nearest Seaway station prior to a Seaway transit.

■ 14. In Part 401, Subpart A, Appendix 1, revise the Caution statement to read as follows:

Appendix 1

Ship Dimensions

* * * * *

Caution: Masters must take into account the ballast draft of the vessel when verifying the maximum permissible dimensions. Bridge wings, antennas, masts and, in some cases, the samson posts or store cranes could be outside the limits of the block diagram and could override the lock wall. Masters and pilots must take this into consideration

and exercise extreme caution when entering or exiting locks to ensure that the vessel does not contact any of the structures on the lock.

* * * * *

Issued at Washington, DC, on February 1, 2016. Saint Lawrence Seaway Development Corporation.

Carrie Lavigne,
Chief Counsel.

[FR Doc. 2016–02168 Filed 2–4–16; 8:45 am]

BILLING CODE 4910–61–P

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Part 52

[EPA–R04–OAR–2015–0152; FRL–9941–95–Region 4]

Air Quality Plans; Georgia; Infrastructure Requirements for the 2010 Sulfur Dioxide National Ambient Air Quality Standard

AGENCY: Environmental Protection Agency (EPA).

ACTION: Proposed rule.

SUMMARY: The Environmental Protection Agency (EPA) is proposing to approve portions of the State Implementation Plan (SIP) submission, submitted by the State of Georgia, through the Georgia Department of Natural Resources (DNR), Environmental Protection Division (GAEPD), on October 22, 2013, and supplemented on July 25, 2014, to demonstrate that the State meets the infrastructure requirements of the Clean Air Act (CAA or Act) for the 2010 1-hour sulfur dioxide (SO₂) national ambient air quality standard (NAAQS). The CAA requires that each state adopt and submit a SIP for the implementation, maintenance and enforcement of each NAAQS promulgated by EPA, which is commonly referred to as an “infrastructure” SIP. GAEPD certified that the Georgia SIP contains provisions that ensure the 2010 1-hour SO₂ NAAQS is implemented, enforced, and maintained in Georgia. EPA is proposing to determine that Georgia’s infrastructure submission, submitted on October 22, 2013, and supplemented on July 25, 2014, addresses certain required infrastructure elements for the 2010 1-hour SO₂ NAAQS.

DATES: Written comments must be received on or before March 7, 2016.

ADDRESSES: Submit your comments, identified by Docket ID No. EPA–R04–OAR–2015–0152, by one of the following methods:

1. *www.regulations.gov*: Follow the on-line instructions for submitting comments.