

DEPARTMENT OF LABOR**Agency Information Collection Activities; Submission for OMB Review; Comment Request; Safety Standards for Roof Bolts in Metal and Nonmetal Mines and Underground Coal Mines**

ACTION: Notice of availability; request for comments.

SUMMARY: The Department of Labor (DOL) is submitting this Mine Safety and Health Administration (MSHA)-sponsored information collection request (ICR) to the Office of Management and Budget (OMB) for review and approval in accordance with the Paperwork Reduction Act of 1995 (PRA). Public comments on the ICR are invited.

DATES: The OMB will consider all written comments that the agency receives on or before April 21, 2025.

ADDRESSES: Written comments and recommendations for the proposed information collection should be sent within 30 days of publication of this notice to www.reginfo.gov/public/do/PRAMain. Find this particular information collection by selecting "Currently under 30-day Review—Open for Public Comments" or by using the search function.

FOR FURTHER INFORMATION CONTACT: Michael Howell by telephone at 202–693–6782, or by email at DOL_PRA_PUBLIC@dol.gov.

SUPPLEMENTARY INFORMATION: Accidents involving falls of roof, face, and rib in underground mines or falls of highwall in surface mines, historically, have been among the leading causes of injuries and deaths. Prevention or control of falls of roof, face, and rib is uniquely difficult because of the variety of conditions encountered in mines that can affect the stability of various types of strata and the changing nature of the forces affecting ground stability at any given operation and time. Roof and rock bolts and accessories are an integral part of ground control systems and are used to prevent the fall of roof, face, and rib. Advancements in technology of roof and rock bolts and accessories have aided in reducing the hazards associated with falls of roof, face, and rib. For additional substantive information about this ICR, see the related notice published in the *Federal Register* on October 23, 2024 (89 FR 84627).

Comments are invited on: (1) whether the collection of information is necessary for the proper performance of the functions of the Department, including whether the information will

have practical utility; (2) the accuracy of the agency's estimates of the burden and cost of the collection of information, including the validity of the methodology and assumptions used; (3) ways to enhance the quality, utility and clarity of the information collection; and (4) ways to minimize the burden of the collection of information on those who are to respond, including the use of automated collection techniques or other forms of information technology.

This information collection is subject to the PRA. A Federal agency generally cannot conduct or sponsor a collection of information, and the public is generally not required to respond to an information collection, unless the OMB approves it and displays a currently valid OMB Control Number. In addition, notwithstanding any other provisions of law, no person shall generally be subject to penalty for failing to comply with a collection of information that does not display a valid OMB Control Number. See 5 CFR 1320.5(a) and 1320.6.

Agency: DOL–MSHA.

Title of Collection: Safety Standards for Roof Bolts in Metal and Nonmetal Mines and Underground Coal Mines.

OMB Control Number: 1219–0121.

Affected Public: Businesses or other for-profits.

Number of Respondents: 484.

Number of Responses: 79,167.

Annual Burden Hours: 740 hours.

Total Estimated Annual Other Costs Burden: \$0.

(Authority: 44 U.S.C. 3507(a)(1)(D))

Michael Howell,

Senior Paperwork Reduction Act Analyst.

[FR Doc. 2025–04721 Filed 3–19–25; 8:45 am]

BILLING CODE 4510–43–P

DEPARTMENT OF LABOR**Mine Safety and Health Administration****Petition for Modification of Application of Existing Mandatory Safety Standards**

AGENCY: Mine Safety and Health Administration, Labor.

ACTION: Notice.

SUMMARY: This notice is a summary of a petition for modification submitted to the Mine Safety and Health Administration (MSHA) by ICG Beckley, LLC.

DATES: All comments on the petition must be received by MSHA's Office of Standards, Regulations, and Variances on or before April 21, 2025.

ADDRESSES: You may submit comments identified by Docket No. MSHA–2025–0032 by any of the following methods:

1. *Federal eRulemaking Portal:* <https://www.regulations.gov>. Follow the instructions for submitting comments for MSHA–2025–0032.

2. *Fax:* 202–693–9441.

3. *Email:* petitioncomments@dol.gov.

4. *Regular Mail or Hand Delivery:*

MSHA, Office of Standards, Regulations, and Variances, Room C3522, 200 Constitution Ave. NW, Washington, DC 20210.

Attention: S. Aromie Noe, Director, Office of Standards, Regulations, and Variances. Persons delivering documents are required to check in at the receptionist's desk. Individuals may inspect copies of the petition and comments during normal business hours at the address listed above. Before visiting MSHA in person, call 202–693–9455 to make an appointment.

FOR FURTHER INFORMATION CONTACT: S. Aromie Noe, Office of Standards, Regulations, and Variances at 202–693–9440 (voice), Petitionsformodification@dol.gov (email), or 202–693–9441 (fax). [These are not toll-free numbers.]

SUPPLEMENTARY INFORMATION: Section 101(c) of the Federal Mine Safety and Health Act of 1977 and title 30 of the Code of Federal Regulations (CFR) part 44 govern the application, processing, and disposition of petitions for modification.

I. Background

Section 101(c) of the Federal Mine Safety and Health Act of 1977 (Mine Act) allows the mine operator or representative of miners to file a petition to modify the application of any mandatory safety standard to a coal or other mine if the Secretary of Labor determines that:

1. An alternative method of achieving the result of such standard exists which will at all times guarantee no less than the same measure of protection afforded the miners of such mine by such standard; or

2. The application of such standard to such mine will result in a diminution of safety to the miners in such mine.

In addition, sections 44.10 and 44.11 of 30 CFR establish the requirements for filing petitions for modification.

II. Petition for Modification

Docket Number: M–2025–021–C.

Petitioner: ICG Beckley, LLC, P.O. Box 49, Eccles, West Virginia 25836.

Mine: Beckley Pocahontas Mine, MSHA ID No. 46–05252, located in Raleigh County, West Virginia.

Regulation Affected: 30 CFR 75.1002(a), Installation of electric equipment and conductors; permissibility.

Modification Request: The petitioner requests a modification of 30 CFR 75.1002(a) to allow the use of unapproved Powered Air Purifying Respirators (PAPRs) in locations within 150 feet of pillar workings or longwall faces. Specifically, the petitioner is requesting to utilize the CleanSpace EX PAPR and sealed motor/blower/battery power pack assembly, and the 3M Versaflo TR-800 Intrinsically Safe PAPR motor/blower and battery with battery pack.

The petitioner states that:

(a) Previously, they have used the 3MTM Airstream TM helmet to provide additional protection for miners against exposure to respirable coal mine dust. There are clear long-term health benefits from using such technology.

(b) 3M elected to discontinue the 3MTM Airstream TM helmet, replacing it with a 3M Versaflo TM TR-800 which benefits from additional features and reduced weight. Because of its reduced weight, it provides significant ergonomic benefits.

(c) For more than 40 years the 3MTM Airstream TM Headgear-Mounted PAPR System has been used by many mine operators to help protect their workers. During those years there have been technological advancements in products and services for industrial applications. 3M indicated that they had faced multiple key component supply disruptions for the Airstream TM product line that created issues with providing acceptable supply service levels. Because of those issues, 3M discontinued the Airstream TM in June 2020, and this discontinuation is global.

(d) 3M announced that February 2020 was the final time to place an order for systems and components and that June 2020 was the final date to purchase Airstream TM components.

(e) Currently there are no replacement 3M PAPRs that meet applicable MSHA standards for permissibility. Electronic equipment used in underground mines in potentially explosive atmospheres is required to be approved by MSHA in accordance with 30 CFR. 3M and other manufacturers offer alternative products for many other environments and applications.

(f) Following the discontinuation, mines that currently use the Airstream TM do not have an MSHA-approved alternative PAPR to provide to miners. One of the benefits of PAPRs is that they provide a constant flow of air inside the headtop or helmet. This constant airflow helps to provide both respiratory protection and comfort in hot working environments.

(g) Application of the standard results in a diminution of safety at the mine.

(h) The 3M Versaflo TR-800 motor/blower and battery qualify as intrinsically safe in the U.S., Canada, and any other country accepting IECEX (International Electrotechnical Commission System for Certification to Standards Relating to Equipment for Use in Explosive Atmospheres) reports. The 3M Versaflo TR-800 has a blower that is UL-certified with an intrinsically safe (IS) rating of Division 1: IS Class I, II, III; Division 1 (includes Division 2) Groups C, D, E, F, G; T4, under the most current standard (UL 60079, 6th Edition, 2013). It is ATEX-certified with an IS rating of "ia." (ATEX refers to European directives for controlling explosive atmospheres.) It is rated and marked with Ex ia I Ma, Ex ia IIB T4 Ga, Ex ia IIIC 135 °C Da, - 20 °C ≤ Ta ≤ +55 °C, under the current standard (IEC 60079).

(i) ICG Beckley Mine seeks modification to also permit the use of the CleanSpace EX powered respirator under the same conditions as it proposed with respect to the 3M Versaflo TR-800. It too has been determined to be intrinsically safe.

(j) The 3M Versaflo TR-800 is not MSHA approved as permissible, and 3M is not pursuing approval.

(k) The CleanSpace EX Power Unit is not MSHA approved as permissible, and CleanSpace is not pursuing approval.

(l) The standards for approval of these respirators are an acceptable alternative to MSHA's standards and provide an equivalent level of protection.

The petitioner proposes the following alternative method:

(a) Affected mine employees shall be trained in the proper use and maintenance of the 3M Versaflo TR-800 and the CleanSpace EX in accordance with established manufacturer guidelines. This training shall alert the affected employee that neither the 3M Versaflo TR-800 nor the CleanSpace EX is approved under 30 CFR part 18 and must be de-energized when 1.0 or more percent methane is detected. The training shall also include the proper method to de-energize these PAPRs. In addition to manufacturer guidelines, the petitioner shall require that mine employees be trained to inspect the units before use to determine if there is any damage to the units that would negatively impact intrinsic safety as well as all stipulations in this petition.

(b) The PAPRs, battery packs, and all associated wiring and connections shall be inspected before use to determine if there is any damage to the units that would negatively impact intrinsic safety. If any defects are found, the PAPR shall be removed from service.

(c) ICG Beckley, LLC shall maintain a separate logbook for the 3M Versaflo

TR-800 and CleanSpace EX PAPRs that shall be kept with the equipment or in a location with other mine record books and shall be made available to MSHA upon request. The equipment shall be examined at least weekly by a qualified person as defined in 30 CFR 75.512-1 and the examination results recorded in the logbook. Since float coal dust is removed by the air filter prior to reaching the motor, the PAPR user shall conduct regular examinations of the filter and perform periodic testing for proper operation of the "high filter load alarm" on the 3M Versaflo TR-800 and the "blocked filter" alarm on the CleanSpace EX. Examination entries may be expunged after one year.

(d) All 3M Versaflo TR-800 and CleanSpace EX PAPRs that shall be used in locations within 150 feet of pillar workings or longwall faces, shall be physically examined prior to initial use, and each unit shall be assigned a unique identification number. Each unit shall be examined by the person to operate the equipment prior to taking the equipment underground to ensure the equipment is being used according to the original equipment manufacturer's recommendations and maintained in a safe operating condition.

(e) The examination for the 3M Versaflo TR-800 shall include:

(1) Check the equipment for any physical damage and the integrity of the case;

(2) Remove the battery and inspect for corrosion;

(3) Inspect the contact points to ensure a secure connection to the battery;

(4) Reinsert the battery and power up and shut down to ensure proper connections;

(5) Check the battery compartment cover or battery attachment to ensure that it is securely fastened; and

(6) For equipment utilizing lithium type cells, ensure that lithium cells and/or packs are not damaged or swelled in size.

(f) The CleanSpace EX does not have an accessible/removable battery. The battery and motor/blower assembly are both contained within the sealed power pack assembly and cannot be removed, reinserted, or fastened. The pre-use examination is limited to inspecting the equipment for indications of physical damage.

(g) ICG Beckley, LLC shall ensure that all 3M Versaflo TR-800 and CleanSpace EX PAPRs are serviced according to the manufacturer's recommendations. Dates of service shall be recorded in the equipment's log book and shall include a description of the work performed.

(h) The 3M Versaflo TR-800 and CleanSpace EX PAPRs that shall be used in locations within 150 feet of pillar workings or longwall faces or in areas where methane may enter the air current, shall not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of the Proposed Decision and Order (PDO) granted by MSHA.

(i) Prior to energizing the 3M Versaflo TR-800 or the CleanSpace EX in locations within 150 feet of pillar workings or longwall faces, methane tests shall be made in accordance with 30 CFR 75.323(a).

(j) All hand-held methane detectors shall be MSHA-approved and maintained in permissible and proper operating conditions as defined by 30 CFR 75.320. All methane detectors shall provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) A qualified person as defined in 30 CFR 75.151 shall continuously monitor for methane immediately before and during the use of the 3M Versaflo TR-800 or CleanSpace EX in locations within 150 feet of pillar workings or longwall faces, or in areas where methane may enter the air current.

(l) Neither the 3M Versaflo TR-800 nor the CleanSpace EX shall be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more of methane is detected while the 3M Versaflo TR-800 or CleanSpace EX is being used, the equipment shall be de-energized immediately and the equipment withdrawn outby the last open crosscut.

(m) ICG Beckley, LLC shall use only the 3M TR-830 Battery Pack, which meets lithium battery safety standard UL 1642 or IEC 62133 in the 3M Versaflo TR-800. The petitioner shall use only the CleanSpace EX Power Unit which meets lithium battery safety standard UL 1642 or IEC 62133 in the CleanSpace EX.

(n) The battery packs shall be "changed out" in intake air outby the last open crosscut. Before each shift when the 3M Versaflo TR-800 or CleanSpace EX is to be used, all batteries and power units for the equipment shall be charged sufficiently so that they are not expected to be replaced on that shift.

(o) The following maintenance and use conditions shall apply to equipment containing lithium-type batteries:

(1) Always correctly use and maintain the lithium-ion battery packs. Neither the 3M TR-830 Battery Pack nor the CleanSpace EX Power Unit shall be disassembled or modified by anyone

other than persons permitted by the manufacturer of the equipment.

(2) The 3M TR-830 Battery Pack shall only be charged in an area free of combustible material, readily monitored, and located on the surface of the mine. The 3M TR-830 Battery Pack is to be charged by either:

(i) 3MTM Battery Charger Kit TR-641N, which includes one 3M Charger Cradle TR-640 and one 3M Power Supply TR-941N, or

(ii) 3M 4-Station Battery Charger Kit TR-644N, which includes four 3M Charger Cradles TR-640 and one 3M 4-Station Battery Charger Base/Power Supply TR-944N.

(3) The CleanSpace EX Power Unit is to be charged only by the CleanSpace Battery Charger EX, Product Code PAF-0066.

(4) The batteries shall not be allowed to get wet. This does not preclude incidental exposure of sealed battery packs.

(5) The batteries shall not be used, charged, or stored in locations where the manufacturer's recommended temperature limits are exceeded. The batteries shall not be placed in direct sunlight or used or stored near a source of heat.

(p) Personnel engaged in the use of the 3M Versaflo TR-800 and CleanSpace EX PAPRs shall be properly trained to recognize the hazards and limitations associated with the use of the equipment in areas where methane could be present. Additionally, personnel shall be trained regarding proper procedures for donning Self Contained Self Rescuers (SCSRs) during a mine emergency while wearing the 3M Versaflo TR-800 or CleanSpace EX. The mine operator shall submit proposed revisions to update the Mine Emergency Evacuation and Firefighting Program of Instruction under 30 CFR 75.1502 to address this issue.

(q) Within 60 days after the PDO granted by MSHA becomes final, ICG Beckley Pocahontas Mine shall submit proposed revisions for its approved 30 CFR part 48 training plans to the Mine Safety and Health Enforcement District Manager. These proposed revisions shall specify initial and refresher training regarding the terms and conditions stated in the PDO granted by MSHA. When training is conducted on the terms and conditions in the PDO granted by MSHA, an MSHA Certificate of Training (Form 5000-23) shall be completed. Comments shall be included on the Certificate of Training indicating that the training received was for use of the 3M Versaflo TR-800 or CleanSpace EX.

(r) All personnel who shall be involved with or affected by the use of the 3M Versaflo TR-800 or CleanSpace EX shall receive training in accordance with 30 CFR 48.7 on the requirements of the PDO granted by MSHA within 60 days of the date the PDO becomes final. Such training shall be completed before any 3M Versaflo TR-800 or CleanSpace EX can be used in locations within 150 feet of pillar workings or longwall faces. The operator shall keep a record of such training and provide such record to MSHA upon request.

(s) ICG Beckley, LLC shall provide annual retraining to all personnel who shall be involved with or affected by the use of the 3M Versaflo TR-800 or CleanSpace EX in accordance with 30 CFR 48.8. The operator shall train new miners on the requirements of the PDO granted by MSHA in accordance with 30 CFR 48.5 and shall train experienced miners on the requirements of the PDO in accordance with 30 CFR 48.6. The operator shall keep a record of such training and provide such record to MSHA upon request.

(t) ICG Beckley, LLC shall post the PDO granted by MSHA in unobstructed locations on the bulletin boards and/or in other conspicuous places where notices to miners are ordinarily posted for a period of not less than 60 consecutive days.

The miners at Beckley Pocahontas Mine are not represented by a labor organization and there are no representatives of the miners at the mine. The petition is posted at the mine.

The petitioner asserts that the alternative method proposed will at all times guarantee no less than the same measure of protection afforded the miners under the mandatory standard.

Song-ae Aromie Noe,

Director, Office of Standards, Regulations, and Variances.

[FR Doc. 2025-04719 Filed 3-19-25; 8:45 am]

BILLING CODE 4520-43-P

DEPARTMENT OF LABOR

Mine Safety and Health Administration

Petition for Modification of Application of Existing Mandatory Safety Standards

AGENCY: Mine Safety and Health Administration, Labor.

ACTION: Notice.

SUMMARY: This notice is a summary of a petition for modification submitted to the Mine Safety and Health Administration (MSHA) by ACI Tygart Valley.