

Year	Vessel name	Details
2024	JOSEPHINE	This certificate authorized the placement of the vessel's sidelights on the elevated pilothouse, 22'-3 ³ / ₁₆ " above the main deck, 16'-5 ¹ / ₁₆ " inboard from the sides of the vessel, and 3'-8 ³ / ₁₆ " forward of the forward masthead light; stern light centered on the aft of the pilot house, 1'-4 ¹ / ₁₆ " forward of amidships, and 40'-5 ¹ / ₄ " above the main deck; and restricted in ability to maneuver (RAM) and not under command (NUC) lights rather than placing these lights on the centerline in a vertical line with the masthead lights, they may be placed 3'-3 ³ / ₈ " outboard from the centerline, starting at a height of 34'-9 ¹³ / ₁₆ " above the main deck with vertical spacing between the RAM/NUC lights being 7'-2 ⁵ / ₈ ".
2024	MOOSE	This certificate authorized the placement of the vessel's sidelights on the elevated pilothouse, 22'-3 ³ / ₁₆ " above the main deck, 16'-5 ¹ / ₁₆ " inboard from the sides of the vessel, and 3'-8 ³ / ₁₆ " forward of the forward masthead light; stern light centered on the aft of the pilot house, 1'-4 ¹ / ₁₆ " forward of amidships, and 40'-5 ¹ / ₄ " above the main deck; and restricted in ability to maneuver (RAM) and not under command (NUC) lights rather than placing these lights on the centerline in a vertical line with the masthead lights, they may be placed 3'-3 ³ / ₈ " outboard from the centerline, starting at a height of 34'-9 ¹³ / ₁₆ " above the main deck with vertical spacing between the RAM/NUC lights being 7'-2 ⁵ / ₈ ".
2024	BEAR	This certificate authorized the placement of the vessel's sidelights on the elevated pilothouse, 22'-3 ³ / ₁₆ " above the main deck, 16'-5 ¹ / ₁₆ " inboard from the sides of the vessel, and 3'-8 ³ / ₁₆ " forward of the forward masthead light; stern light centered on the aft of the pilot house, 1'-4 ¹ / ₁₆ " forward of amidships, and 40'-5 ¹ / ₄ " above the main deck; and restricted in ability to maneuver (RAM) and not under command (NUC) lights rather than placing these lights on the centerline in a vertical line with the masthead lights, they may be placed 3'-3 ³ / ₈ " outboard from the centerline, starting at a height of 34'-9 ¹³ / ₁₆ " above the main deck with vertical spacing between the RAM/NUC lights being 7'-2 ⁵ / ₈ ".
2024	OCEANOGRAPHER	This certificate authorized placement of the vessels masthead light on the main mast, 102'-7.25" aft and 43'-9.75" above the forward masthead light; stern light on the furthest aft location being the port side exhaust stack at a height of 39'-3.75" from the main deck; and restricted in ability to maneuver (RAM) and not under command (NUC) lights, rather than placing these lights on the centerline in a vertical line with the masthead lights, they may be placed 2'-1" off centerline starting 67'-10.5" above the main deck and vertically spaced at 6'-6.75".
2024	DISCOVERER	This certificate authorized placement of the vessels after masthead light on the main mast, 102'-7.25" aft and 43'-9.75" above the forward masthead light; sternlight on the furthest aft location being the port side exhaust stack at a height of 39'-3.75" from the main deck; and restricted in ability to maneuver (RAM) and not under command (NUC) lights—rather than placing these lights on the centerline in a vertical line with the masthead lights, they may be placed 2'-1" off centerline starting 67'-10.5" above the main deck and vertically spaced at 6'-6.75".

The Chief of Prevention Division of the Eighth Coast Guard District, U.S. Coast Guard, certifies that the vessels listed above are of special construction or purpose and are unable to comply fully with the requirements of the provisions enumerated in the 72 COLREGS, without interfering with the normal operation, construction, or design of the vessels. The Chief of Prevention Division further finds and certifies that the listed vessels are in the closest possible compliance with the applicable provisions of the 72 COLREGS.⁵

This notice is issued under authority of 33 U.S.C. 1605(c) and 33 CFR 81.18.

Dated: June 16, 2025.

J.E. Fothergill,

Commander, U.S. Coast Guard, Chief of Prevention, Acting, By direction of the Commander, Eighth Coast Guard District.

[FR Doc. 2025-11918 Filed 6-26-25; 8:45 am]

BILLING CODE 9110-04-P

DEPARTMENT OF HOMELAND SECURITY

Coast Guard

[Docket No. USCG-2025-0091]

Certificates of Alternative Compliance for the Eighth Coast Guard District

AGENCY: Coast Guard, DHS.

ACTION: Notification of issuance of certificates of alternative compliance.

SUMMARY: The Coast Guard announces that the Eighth Coast Guard District's Prevention Division has issued certificates of alternative compliance from the International Regulations for Preventing Collisions at Sea, 1972 (72 COLREGS), to vessels of special construction or purpose that cannot fully comply with the light, shape, and sound signal provisions of 72 COLREGS without interfering with the vessel's design and construction. We are issuing this notice because its publication is required by statute. This notification of issuance of certificates of alternative compliance promotes the Coast Guard's marine safety mission.

DATES: These Certificates of Alternative Compliance were issued between August 2024 and December 2024.

FOR FURTHER INFORMATION CONTACT: For information or questions about this notice call or email Lieutenant Jenifer Abiona, District Eight, Prevention Division, U.S. Coast Guard, telephone 206-827-2691, email Jenifer.V.Abiona@uscg.mil.

SUPPLEMENTARY INFORMATION: The United States is signatory to the International Maritime Organization's International Regulations for Preventing Collisions at Sea, 1972 (72 COLREGS), as amended. The special construction or purpose of some vessels makes them unable to comply with the light, shape, or sound signal provisions of the 72 COLREGS. Under statutory law, however, specified 72 COLREGS provisions are not applicable to a vessel of special construction or purpose if the Coast Guard determines that the vessel cannot comply fully with those requirements without interfering with the special function of the vessel.¹

⁵ 33 U.S.C. 1605(a); 33 CFR 81.9.

¹ 33 U.S.C. 1605.

The owner, builder, operator, or agent of a special construction or purpose vessel may apply to the Coast Guard District Office in which the vessel is being built or operated for a determination that compliance with alternative requirements is justified,²

and the Chief of the Prevention Division would then issue the applicant a certificate of alternative compliance (COAC) if he or she determines that the vessel cannot comply fully with 72 COLREGS light, shape, and sound signal provisions without interference with the

vessel's special function.³ If the Coast Guard issues a COAC, it must publish notice of this action in the **Federal Register**.⁴

The Eighth Coast Guard District has issued COACs to the following vessels from August 2024 to December 2024:

Year	Vessel name	Details
2024	LEN O'CONNOR	This certificate authorized the placement of the vessel's sidelights on the elevated pilothouse roof, 34'-9" above the main deck, 7'-1/2" inboard from the sides of the vessel, and 4'-5/8" aft of the forward masthead light.
2024	HOS RUGER	This certificate authorized the placement of the vessel's aft masthead light positioned on the main mast above the pilothouse at a distance of 21'-9 1/16" aft of the forward masthead light and 67'-10 1/16" above the main deck; and sternlight positioned centerline on the aft end of the pilot at a distance of 36'-10 1/8" above the main deck and 17'-2 7/16" aft of the aft masthead light.
2024	HOS BENELLI	This certificate authorized the placement of the vessel's aft masthead light positioned on the main mast above the pilothouse at a distance of 21'-9 1/16" aft of the forward masthead light and 67'-10 1/16" above the main deck; and sternlight positioned centerline on the aft end of the pilot at a distance of 36'-10 1/8" above the main deck and 17'-2 7/16" aft of the aft masthead light.
2024	USNS ROBERT BALLARD	This certificate authorized the placement of the vessel's sternlight positioned centerline on the elevated pilothouse at a distance of 21' above the main deck; and aft masthead light positioned centerline at a distance of 156'-9" aft of the Forward Masthead Light and 69'-5" above the main deck.
2024	MARY JANE MORAN	This certificate authorized the placement of the vessel's sidelights on the elevated pilothouse, positioned 12' from the side of the vessel, and 19'-6 13/16" above the main deck; stern light aft side of the elevated pilothouse, 1'-4" starboard of centerline and 20'-10 1/8" above the main deck; masthead light centerline on the elevated pilothouse, 39' above the main deck when upright, and 25'-10 3/8" above the main deck when mast is in the lowered position during ship assist work in order to prevent damage when working in close proximity to a ship's bow/stern flare; restricted in ability to maneuver (RAM) and not under command (NUC) lights placed 1'-3" forward of the masthead lights starting at a height of 27'-6 1/16" above the main deck with vertical spacing between the RAM/NUC lights being 3'-3 3/8".
2024	HOS RUNNING BUCK	This certificate authorized the placement of the vessel's aft masthead light positioned on the main mast above the pilothouse at a distance of 21'-5 1/4" aft of the forward masthead light and at a vertical distance of 37'-1 1/8" from the forward masthead light; and sternlight positioned centerline on the aft edge of the fo'c'sle deck at a distance of 12'-9" above the main deck and 176'-6" forward of the vessel's stern.
2024	ARTEMIS	This certificate authorized placement of the vessel's masthead light positioned centered on the elevated pilot house, 22'-7 1/8" above the main deck when the mast is in the lowered position; and 39'-4 5/8" above the main deck; sidelights on the elevated pilot house, 10'-1" outboard from the centerline of the vessel, and 12'-5 5/8" above the main deck; and stern light based on the dual direction operational towing vessel: ahead direction—stern light centered on the pilot house at a height of 22'-7 1/8" for pushing ahead operations (e.g., pushing, hauling alongside, and pulling); and astern direction—stern light placed on the main mast at a height of 27'-9 5/8" for astern operations (e.g., towing).
2024	BAHIA GULF	This certificate authorized placement of the vessel's masthead light positioned on the mast above the pilot house at a height of 39'-4 5/8" above the hull and when the mast is in the lowered position, a height of 22'-7 1/8" above the hull; sidelights positioned near the pilot house at a height of 12'-5 5/8" above the hull and 10'-1" outboard from the centerline of the vessel; sternlight based on the towing vessel being dual direction operation: ahead direction—Sternlight centered on the pilot house at a height of 22'-7 1/8" for pushing ahead operations (e.g., pushing, hauling alongside, and pulling); and astern direction—Sternlight placed on the mast at a height of 27'-9 5/8" for astern operations (e.g., towing); and Restricted in Ability to Maneuver (RAM) and Not Under Command (NUC) lights placed 1'-6" off centerline starting at 25'-5 1/8" above the hull and vertically spaced at 6'-7".

The Chief of Prevention Division of the Eighth Coast Guard District, U.S. Coast Guard, certifies that the vessels listed above are of special construction or purpose and are unable to comply fully with the requirements of the provisions enumerated in the 72 COLREGS, without interfering with the normal operation, construction, or

design of the vessels. The Chief of Prevention Division, further finds and certifies that the listed vessels are in the closest possible compliance with the applicable provisions of the 72 COLREGS.⁵

This notice is issued under authority of 33 U.S.C. 1605(c) and 33 CFR 81.18.

Dated: June 16, 2025.

J.E. Fothergill,

Commander, U.S. Coast Guard, Chief of Prevention, Acting, By direction of the Commander, Eighth Coast Guard District.

[FR Doc. 2025-11914 Filed 6-26-25; 8:45 am]

BILLING CODE 9110-04-P

² 33 CFR 81.5.

³ 33 CFR 81.9.

⁴ 33 U.S.C. 1605(c) and 33 CFR 81.18.

⁵ 33 U.S.C. 1605(a); 33 CFR 81.9.