(1) The Director of the Federal Register approves the incorporation by reference of Chapter 05–10–10 of the BAE Systems (Operations) Limited J41 Airplane Maintenance Manual, Revision 23, dated February 15, 2005, in accordance with 5 U.S.C. 552(a) and 1 CFR part 51.

(2) On August 3, 2004 (69 FR 38816, June 29, 2004), the Director of the Federal Register approved the incorporation by reference of BAE Systems (Operations) Limited Service Bulletin J41–05–001, Revision 2, dated March 15, 2002; BAE Systems (Operations) Limited Service Bulletin J41–05–001, Revision 3, dated January 9, 2004; and BAE Systems (Operations) Limited Service Bulletin J41–32–078, dated April 12, 2002.

(3) To get copies of the service information, contact British Aerospace Regional Aircraft American Support, 13850 Mclearen Road, Herndon, Virginia 20171. You may review copies at the Docket Management Facility, U.S. Department of Transportation, 400 Seventh Street SW., room PL-401, Nassif Building, Washington, DC; on the Internet at http://dms.dot.gov; or at the National Archives and Records Administration (NARA). For information on the availability of this material at the NARA, call (202) 741–6030, or go to http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html.

Issued in Renton, Washington, on September 9, 2005.

Kalene C. Yanamura.

Acting Manager, Transport Airplane Directorate, Aircraft Certification Service. [FR Doc. 05–18519 Filed 9–20–05; 8:45 am] BILLING CODE 4910–13–P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 39

[Docket No. FAA-2005-21861; Directorate Identifier 2005-NM-093-AD; Amendment 39-14281; AD 2005-19-16]

RIN 2120-AA64

Airworthiness Directives; Airbus Model A320–111 Airplanes and Model A320– 200 Series Airplanes

AGENCY: Federal Aviation Administration (FAA), Department of Transportation (DOT).

ACTION: Final rule.

SUMMARY: The FAA is adopting a new airworthiness directive (AD) for certain Airbus Model A320–111 airplanes and Model A320–200 series airplanes. This AD requires installing a bonding strip between each of the two water scavenge jet pumps of the center fuel tank and the rear spar in section 21. This AD results from the results of fuel system reviews conducted by the manufacturer. We are issuing this AD to prevent an ignition

source for fuel vapor in the wing, which could result in fire or explosion in the center wing fuel tank.

DATES: This AD becomes effective October 26, 2005.

The Director of the Federal Register approved the incorporation by reference of a certain publication listed in the AD as of October 26, 2005.

ADDRESSES: You may examine the AD docket on the Internet at http://dms.dot.gov or in person at the Docket Management Facility, U.S. Department of Transportation, 400 Seventh Street SW., Nassif Building, Room PL-401, Washington, DC.

Contact Airbus, 1 Rond Point Maurice Bellonte, 31707 Blagnac Cedex, France, for service information identified in this AD.

FOR FURTHER INFORMATION CONTACT: Dan Rodina, Aerospace Engineer, International Branch, ANM-116, FAA, Transport Airplane Directorate, 1601 Lind Avenue, SW., Renton, Washington 98055-4056; telephone (425) 227-2125; fax (425) 227-1149.

SUPPLEMENTARY INFORMATION:

Examining the Docket

You may examine the airworthiness directive (AD) docket on the Internet at http://dms.dot.gov or in person at the Docket Management Facility office between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays. The Docket Management Facility office (telephone (800) 647–5227) is located on the plaza level of the Nassif Building at the street address stated in the ADDRESSES section.

Discussion

The FAA issued a notice of proposed rulemaking (NPRM) to amend 14 CFR part 39 to include an AD that would apply to certain Airbus Model A320–111 airplanes and Model A320–200 series airplanes. That NPRM was published in the **Federal Register** on July 19, 2005 (70 FR 41350). That NPRM proposed to require installing a bonding strip between each of the two water scavenge jet pumps of the center fuel tank and the rear spar in section 21.

Comments

We provided the public the opportunity to participate in the development of this AD. We have considered the comment received. The commenter supports the NPRM.

Conclusion

We have carefully reviewed the available data, including the comment received, and determined that air safety and the public interest require adopting the AD as proposed.

Costs of Compliance

This AD will affect about 371 airplanes of U.S. registry. The actions will take about 1 work hour per airplane, at an average labor rate of \$65 per work hour. The manufacturer will supply required parts at no charge. Based on these figures, the estimated cost of the AD for U.S. operators is \$24,115, or \$65 per airplane.

Authority for This Rulemaking

Title 49 of the United States Code specifies the FAA's authority to issue rules on aviation safety. Subtitle I, Section 106, describes the authority of the FAA Administrator. Subtitle VII, Aviation Programs, describes in more detail the scope of the Agency's authority.

We are issuing this rulemaking under the authority described in Subtitle VII, Part A, Subpart III, Section 44701, "General requirements." Under that section, Congress charges the FAA with promoting safe flight of civil aircraft in air commerce by prescribing regulations for practices, methods, and procedures the Administrator finds necessary for safety in air commerce. This regulation is within the scope of that authority because it addresses an unsafe condition that is likely to exist or develop on products identified in this rulemaking action.

Regulatory Findings

We have determined that this AD will not have federalism implications under Executive Order 13132. This AD will not have a substantial direct effect on the States, on the relationship between the national government and the States, or on the distribution of power and responsibilities among the various levels of government.

For the reasons discussed above, I certify that this AD:

- (1) Is not a "significant regulatory action" under Executive Order 12866;
- (2) Is not a "significant rule" under DOT Regulatory Policies and Procedures (44 FR 11034, February 26, 1979); and
- (3) Will not have a significant economic impact, positive or negative, on a substantial number of small entities under the criteria of the Regulatory Flexibility Act.

We prepared a regulatory evaluation of the estimated costs to comply with this AD and placed it in the AD docket. See the **ADDRESSES** section for a location to examine the regulatory evaluation.

List of Subjects in 14 CFR Part 39

Air transportation, Aircraft, Aviation safety, Incorporation by reference, Safety.

Adoption of the Amendment

■ Accordingly, under the authority delegated to me by the Administrator, the FAA amends 14 CFR part 39 as follows:

PART 39—AIRWORTHINESS DIRECTIVES

■ 1. The authority citation for part 39 continues to read as follows:

Authority: 49 U.S.C. 106(g), 40113, 44701.

§ 39.13 [Amended]

■ 2. The Federal Aviation Administration (FAA) amends § 39.13 by adding the following new airworthiness directive (AD):

2005–19–16 Airbus: Amendment 39–14281. Docket No. FAA–2005–21861; Directorate Identifier 2005–NM–093–AD.

Effective Date

(a) This AD becomes effective October 26, 2005.

Affected ADs

(b) None.

Applicability

(c) This AD applies to Airbus Model A320–111, -211, -212, -214, -231, -232, and -233 airplanes, certificated in any category; except those airplanes on which Airbus Modification 25513 has been accomplished in production.

Unsafe Condition

(d) This AD results from fuel system reviews conducted by the manufacturer. We are issuing this AD to prevent an ignition source for fuel vapor in the wing, which could result in fire or explosion in the adjacent wing fuel tank.

Compliance

(e) You are responsible for having the actions required by this AD performed within the compliance times specified, unless the actions have already been done.

Installation of Bonding Strips

(f) Within 56 months after the effective date of this AD, install a bonding strip between each of the two water scavenge jet pumps of the center fuel tank and the rear spar in section 21, in accordance with the Accomplishment Instructions of Airbus Service Bulletin A320–28–1067, Revision 02, dated January 27, 1997.

Alternative Methods of Compliance (AMOCs)

(g) The Manager, International Branch, ANM–116, Transport Airplane Directorate, FAA, has the authority to approve AMOCs for this AD, if requested in accordance with the procedures found in 14 CFR 39.19.

Related Information

(h) French airworthiness directive F–2005–056, dated April 13, 2005, also addresses the subject of this AD.

Material Incorporated by Reference

(i) You must use Airbus Service Bulletin A320-28-1067, Revision 02, dated January 27, 1997, to perform the actions that are required by this AD, unless the AD specifies otherwise. The Director of the Federal Register approved the incorporation by reference of this document in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. Contact Airbus, 1 Rond Point Maurice Bellonte, 31707 Blagnac Cedex, France, for a copy of this service information. You may review copies at the Docket Management Facility, U.S. Department of Transportation, 400 Seventh Street SW., room PL-401, Nassif Building, Washington, DC; on the Internet at http://dms.dot.gov; or at the National Archives and Records Administration (NARA). For information on the availability of this material at the NARA, call (202) 741-6030, or go to http://www.archives.gov/ federal_register/code_of_federal_regulations/ ibr_locations.html.

Issued in Renton, Washington, on September 9, 2005.

Kalene C. Yanamura,

Acting Manager, Transport Airplane Directorate, Aircraft Certification Service. [FR Doc. 05–18520 Filed 9–20–05; 8:45 am]

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 39

[Docket No. FAA-2005-22453; Directorate Identifier 2002-NM-139-AD; Amendment 39-14278; AD 2005-19-13]

RIN 2120-AA64

Airworthiness Directives; British Aerospace Model HS 748 Airplanes

AGENCY: Federal Aviation Administration (FAA), Department of Transportation (DOT).

ACTION: Final rule; request for comments.

SUMMARY: The FAA is adopting a new airworthiness directive (AD) for all British Aerospace Model HS 748 airplanes. This AD requires modifying the undercarriage of the nose landing gear (NLG). This AD results from a report that pintle pins could be installed in an incorrect manner during maintenance without maintenance personnel being aware (or having feedback) that the pin was installed incorrectly. We are issuing this AD to prevent jamming or collapse of the NLG, which could result in damage to the airplane structure or injury to passengers or crew.

DATES: Effective October 6, 2005.

The Director of the Federal Register approved the incorporation by reference

of a certain publication listed in the AD as of October 6, 2005.

We must receive comments on this AD by November 21, 2005.

ADDRESSES: Use one of the following addresses to submit comments on this AD.

- DOT Docket Web site: Go to http://dms.dot.gov and follow the instructions for sending your comments electronically.
- Government-wide rulemaking Web site: Go to http://www.regulations.gov and follow the instructions for sending your comments electronically.
- Mail: Docket Management Facility; U.S. Department of Transportation, 400 Seventh Street SW., Nassif Building, Room PL-401, Washington, DC 20590.
 - Fax: (202) 493-2251.
- Hand Delivery: Room PL-401 on the plaza level of the Nassif Building, 400 Seventh Street SW., Washington, DC, between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays.

Contact British Aerospace Regional Aircraft American Support, 13850 Mclearen Road, Herndon, Virginia 20171, for service information identified in this AD.

FOR FURTHER INFORMATION CONTACT:

Todd Thompson, Aerospace Engineer, International Branch, ANM–116, FAA, Transport Airplane Directorate, 1601 Lind Avenue, SW., Renton, Washington 98055–4056; telephone (425) 227–1175; fax (425) 227–1149.

SUPPLEMENTARY INFORMATION:

Discussion

The Civil Aviation Authority (CAA), which is the airworthiness authority for the United Kingdom, notified us that an unsafe condition may exist on all British Aerospace Model HŠ 748 Airplanes. The CAA advises that failure to follow the airplane's maintenance manual instructions for installing the nose landing gear (NLG) could result in incorrect assembly of the NLG. Incorrect assembly may result in the pintle pin being unlocked, so that it is free to migrate from its support housing. It is possible to install the pintle pin in an incorrect configuration without any knowledge or suspicion that the pin was installed incorrectly. Incorrect assembly of the pin, if not corrected, could result in jamming or collapse of the NLG, which could result in damage to the airplane structure or injury to passengers or crew.

Relevant Service Information

British Aerospace has issued BAE Systems (Operations) Limited Service Bulletin HS748–32–104, dated April 9, 2002. The service bulletin describes