

applicants' burden is 612 hours and the debtors' burden is 16,616 hours.

If additional information is required contact: Melody Braswell, Department Clearance Officer, United States Department of Justice, Justice Management Division, Policy and Planning Staff, Two Constitution Square, 145 N Street NE, 3E.405A, Washington, DC 20530.

Dated: October 8, 2019.

Melody Braswell,

Department Clearance Officer for PRA, U.S. Department of Justice.

[FR Doc. 2019-22360 Filed 10-11-19; 8:45 am]

BILLING CODE 4410-40-P

DEPARTMENT OF JUSTICE

[OMB Number 1105-0084]

Agency Information Collection Activities; Proposed eCollection eComments Requested; Extension, Without Change, of a Currently Approved Collection

AGENCY: United States Trustee Program, Department of Justice.

ACTION: 30 Day notice.

SUMMARY: The Department of Justice, United States Trustee Program, is submitting the following information collection request to the Office of Management and Budget (OMB) for review and approval in accordance with the Paperwork Reduction Act of 1995.

DATES: The Department of Justice encourages public comment and will accept input until November 14, 2019.

FOR FURTHER INFORMATION CONTACT: If you have additional comments especially on the estimated public burden or associated response time, suggestions, or need a copy of the proposed information collection instrument with instructions or additional information, please contact Juliet Drake, Deputy Assistant Director, Executive Office for United States Trustees, 441 G Street NW, Suite 6150, Washington, DC 20530, Juliet.Drake@usdoj.gov, (202) 307-3698. Written comments and/or suggestions can also be sent to the Office of Management and Budget, Office of Information and Regulatory Affairs, Attention Department of Justice Desk Officer, Washington, DC 20503 or sent to OIRA_submissions@omb.eop.gov.

SUPPLEMENTARY INFORMATION: Written comments and suggestions from the public and affected agencies concerning the proposed collection of information are encouraged. Your comments should address one or more of the following four points:

- Evaluate whether the proposed collection of information is necessary for the proper performance of the functions of the United States Trustee Program, including whether the information will have practical utility;
- Evaluate the accuracy of the agency's estimate of the burden of the proposed collection of information, including the validity of the methodology and assumptions used;
- Evaluate whether and if so how the quality, utility, and clarity of the information to be collected can be enhanced; and
- Minimize the burden of the collection of information on those who are to respond, including through the use of appropriate automated, electronic, mechanical, or other technological collection techniques or other forms of information technology, *e.g.*, permitting electronic submission of responses.

Overview of This Information Collection

1. Type of Information Collection:

Extension, without change, of a currently approved collection.

2. The Title of the Form/Collection:

Application for Approval as a Nonprofit Budget and Credit Counseling Agency (Application).

3. The agency form number, if any, and the applicable component of the Department sponsoring the collection:

There is no agency form number for this collection. The applicable component within the Department of Justice is the United States Trustee Program.

4. *Affected public who will be asked or required to respond, as well as a brief abstract:* Nonprofit agencies that wish to offer credit counseling services pursuant to the Bankruptcy Abuse Prevention and Consumer Protection Act of 2005 ("BAPCPA"), Public Law 109-8, 119 Stat. 23, 37, 38 (April 20, 2005), and codified at 11 U.S.C. 109(h) and 111, and Application Procedures and Criteria for Approval of Nonprofit Budget and Credit Counseling Agencies by United States Trustees, 78 FR 16,138 (March 14, 2013) (Rule).

The BAPCPA requires any individual who wishes to file for bankruptcy to obtain credit counseling, within 180 days before filing for bankruptcy relief, from a nonprofit budget and credit counseling agency that has been approved by the United States Trustee. The Application collects information from such agencies in order to ensure compliance with the law and the Rule.

5. *An estimate of the total number of respondents and the amount of time estimated for an average respondent to respond:* It is estimated that 86

respondents will complete the Application; initial applicants will complete the Application in approximately ten (10) hours, while renewal applicants will complete the Application in approximately four (4) hours.

6. *An estimate of the total public burden (in hours) associated with the collection:* The estimated public burden associated with this collection is 362 hours.

If additional information is required contact: Melody Braswell, Department Clearance Officer, United States Department of Justice, Justice Management Division, Policy and Planning Staff, Two Constitution Square, 145 N Street NE, 3E.405A, Washington, DC 20530.

Dated: October 8, 2019.

Melody Braswell,

Department Clearance Officer for PRA, U.S. Department of Justice.

[FR Doc. 2019-22359 Filed 10-11-19; 8:45 am]

BILLING CODE 4410-40-P

DEPARTMENT OF LABOR

Mine Safety and Health Administration

Petitions for Modification of Application of Existing Mandatory Safety Standards

AGENCY: Mine Safety and Health Administration, Labor.

ACTION: Notice.

SUMMARY: This notice is a summary of petitions for modification submitted to the Mine Safety and Health Administration (MSHA) by the parties listed below.

DATES: All comments on the petitions must be received by MSHA's Office of Standards, Regulations, and Variances on or before November 14, 2019.

ADDRESSES: You may submit your comments, identified by "docket number" on the subject line, by any of the following methods:

1. *Electronic Mail:* zzMSHA-comments@dol.gov. Include the docket number of the petition in the subject line of the message.

2. *Facsimile:* 202-693-9441.

3. *Regular Mail or Hand Delivery:* MSHA, Office of Standards, Regulations, and Variances, 201 12th Street South, Suite 4E401, Arlington, Virginia 22202-5452, Attention: Sheila McConnell, Director, Office of Standards, Regulations, and Variances. Persons delivering documents are required to check in at the receptionist's desk in Suite 4E401. Individuals may

inspect copies of the petition and comments during normal business hours at the address listed above.

MSHA will consider only comments postmarked by the U.S. Postal Service or proof of delivery from another delivery service such as UPS or Federal Express on or before the deadline for comments.

FOR FURTHER INFORMATION CONTACT:

Sheila McConnell, Office of Standards, Regulations, and Variances at 202-693-9440 (voice), *McConnell.Sheila.A@dol.gov* (email), or 202-693-9441 (facsimile). [These are not toll-free numbers.]

SUPPLEMENTARY INFORMATION: Section 101(c) of the Federal Mine Safety and Health Act of 1977 and Title 30 of the Code of Federal Regulations Part 44 govern the application, processing, and disposition of petitions for modification.

I. Background

Section 101(c) of the Federal Mine Safety and Health Act of 1977 (Mine Act) allows the mine operator or representative of miners to file a petition to modify the application of any mandatory safety standard to a coal or other mine if the Secretary of Labor determines that:

1. An alternative method of achieving the result of such standard exists which will at all times guarantee no less than the same measure of protection afforded the miners of such mine by such standard; or

2. That the application of such standard to such mine will result in a diminution of safety to the miners in such mine.

In addition, the regulations at 30 CFR 44.10 and 44.11 establish the requirements and procedures for filing petitions for modification.

II. Petitions for Modification

Docket Number: M-2019-050-C.

Petitioner: Peabody Gateway North Mining LLC, Six PPG Place, Suite 830, Pittsburgh, PA 15222.

Mines: Gateway North Mine, MSHA I.D. No. 11-03235, located in Randolph County, Illinois.

Regulation Affected: 30 CFR 75.500(d) (Permissible electric equipment).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, in or inby the last open crosscut.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary.

(2) The operator utilizes the continuous mining method.

(3) Mechanical surveying equipment has been obsolete for a number of years. Such equipment of acceptable quality is not commercially available. Further, it is difficult, if not impossible, to have such equipment serviced or repaired.

(4) Accurate surveying is critical to the safety of the miners at the mine. Electronic surveying equipment is, at a minimum, 8 to 10 times more accurate than mechanical equipment.

(5) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater in or inby the last open crosscut, subject to this petition:

—Sokkia CX103

—TopCon GPT 3209 NW

—TopCon GTS 235 W

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites, data loggers, and laser distance meters. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used in or inby the last open crosscut will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used in or inby the last open crosscut will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn outby the last open crosscut. All requirements of 30 CFR 75.323 will be complied with prior to entering in or inby the last open crosscut.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment in or inby the last open crosscut, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of accumulated float coal dust. If the rock-dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment in or inby the last open crosscut, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used in or inby the open crosscut when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment in or inby the last open crosscut. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be changed out or charged in fresh air outby the last open crosscut. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment in or inby the last open crosscut, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, in or inby the last open crosscut is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment in or inby the last open crosscut. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000-23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used in or inby the last open crosscut, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

- On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.
- Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.
- Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine's ventilation system that causes the ventilation system not to function in accordance with the mine's approved ventilation plan.
- If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.
- Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.
- All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.
- The operator will provide annual retraining to all personnel who will be involved with or affected by

surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Docket Number: M–2019–051–C.

Petitioner: Peabody Gateway North Mining LLC, Six PPG Place, Suite 830, Pittsburgh, PA 15222.

Mines: Gateway North Mine, MSHA I.D. No. 11–03235, located in Randolph County, Illinois.

Regulation Affected: 30 CFR 75.507–1(a) (Electric equipment other than power-connection points; outby the last open crosscut; return air; permissibility requirements).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, in return airways.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200(a), use of the most practical and accurate surveying equipment is necessary.

(2) The operator utilizes the continuous miner method of mining.

(3) Mechanical surveying equipment has been obsolete for a number of years. Such equipment of acceptable quality is not commercially available. Further it is difficult, if not impossible, to have such equipment serviced or repaired.

(4) Accurate surveying is critical to the safety of the miners at the mine. Electronic surveying equipment is, at a minimum, 8 to 10 times more accurate than mechanical equipment.

(5) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater in return airways, subject to this petition:

—Sokkia CX103

—TopCon GPT 3209 NW

—TopCon GTS 235 W

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites, data loggers, and laser distance meters. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used in return airways will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used in return

airways will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn out of return airways. All requirements of 30 CFR 75.323 will be complied with prior to entering in return airways.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment in return airways, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be sufficiently rock-dusted and for the presence of accumulated float coal dust. If the rock dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment in return airways, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used in return airways when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment in return airways. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified

person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be changed out or charged in fresh air out of return airways. Replacement batteries will be carried only in the compartment provided for a spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment in return airways, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, in return airways is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment in return airways. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000-23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes

final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used in return airways, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

- On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.

- Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.

- Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine's ventilation system that causes the ventilation system not to function in accordance with the mine's approved ventilation plan.

- If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished

and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.

- Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.

- All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.

- The operator will provide annual retraining to all personnel who will be involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Docket Number: M-2019-052-C.

Petitioner: Peabody Gateway North Mining LLC, Six PPG Place, Suite 830, Pittsburgh, PA 15222.

Mines: Gateway North Mine, MSHA I.D. No. 11-03235, located in Randolph County, Illinois.

Regulation Affected: 30 CFR 75.1002(a) (Installation of electric equipment and conductors; permissibility).

Modification Request: The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment including, but not

limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers, within 150 feet of pillar workings and longwall faces.

The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372, 75.1002(a), and 75.1200, use of the most practical and accurate surveying equipment is necessary. It is necessary to determine the exact location and extent of mine workings to ensure the safety of miners in active mines and to protect miners in future mines which may mine in close proximity to the active mines.

(2) The operator utilizes the continuous miner method of mining.

(3) Mechanical surveying equipment has been obsolete for a number of years. Such equipment of acceptable quality is not commercially available. Further it is difficult, if not impossible, to have such equipment serviced or repaired.

(4) Accurate surveying is critical to the safety of the miners at the mine. Electronic surveying equipment is, at a minimum, 8 to 10 times more accurate than mechanical equipment.

(5) Application of the existing standard would result in a diminution of safety to miners. Underground mining by its nature, size, and complexity of mine plans requires that accurate and precise measurements be completed in a prompt and efficient manner.

As an alternative to the existing standard, the petitioner proposes the following:

(a) The operator may use the following total stations and theodolites and similar low-voltage battery-operated total stations and theodolites if they have an ingress protection (IP) rating of 66 or greater within 150 feet of pillar workings or longwall faces, subject to this petition:

—Sokkia CX103

—TopCon GPT 3209 NW

—TopCon GTS 235 W

(b) The nonpermissible electronic surveying equipment is low-voltage or battery-powered nonpermissible total stations and theodolites, data loggers, and laser distance meters. All nonpermissible electronic total stations and theodolites will have an IP 66 or greater rating.

(c) The operator will maintain a logbook for electronic surveying equipment with the equipment, or in the location where mine record books are kept, or in the location where the surveying record books are kept. The logbook will contain the date of manufacture and/or purchase of each

particular piece of electronic surveying equipment. The logbook will be made available to MSHA on request.

(d) All nonpermissible electronic surveying equipment to be used within 150 feet of pillar workings or longwall faces will be examined by the person who operates the equipment prior to taking the equipment underground to ensure the equipment is being maintained in a safe operating condition. The result of these examinations will be recorded in the logbook and will include:

(i) Checking the instrument for any physical damage and the integrity of the case;

(ii) Removing the battery and inspecting for corrosion;

(iii) Inspecting the contact points to ensure a secure connection to the battery;

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections; and

(v) Checking the battery compartment cover or battery attachment to ensure that it is securely fastened.

(e) The equipment will be examined at least weekly by a qualified person, as defined in 30 CFR 75.153. The examination results will be recorded weekly in the equipment logbook and will be maintained for at least 1 year.

(f) The operator will ensure that all nonpermissible electronic surveying equipment is serviced according to the manufacturer's recommendations. Dates of service will be recorded in the equipment's logbook and will include a description of the work performed.

(g) The nonpermissible electronic surveying equipment used within 150 feet of pillar workings or longwall faces will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions of this petition.

(h) Nonpermissible electronic surveying equipment will not be used if methane is detected in concentrations at or above 1.0 percent. When 1.0 percent or more methane is detected while such equipment is being used, the equipment will be de-energized immediately and withdrawn further than 150 feet from pillar workings and longwall faces. All requirements of 30 CFR 75.323 will be complied with prior to entering within 150 feet of pillar workings or longwall faces.

(i) Prior to setting up and energizing nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces, the surveyor(s) will conduct a visual examination of the immediate area for evidence that the area appears to be

sufficiently rock-dusted and for the presence of accumulated float coal dust. If the rock dusting appears insufficient or the presence of accumulated float coal dust is observed, the equipment will not be energized until sufficient rock-dust has been applied and/or the accumulations of float coal dust have been cleaned up. If nonpermissible electronic surveying equipment is to be used in an area not rock-dusted within 40 feet of a working face where a continuous mining machine is used, the area will be rock-dusted prior to energizing the nonpermissible electronic surveying equipment.

(j) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition, as defined in 30 CFR 75.320. All methane detectors will provide visual and audible warnings when methane is detected at or above 1.0 percent.

(k) Prior to energizing nonpermissible electronic surveying equipment within 150 feet of pillar workings and longwall faces, methane tests will be made in accordance with 30 CFR 75.323(a). Nonpermissible electronic surveying equipment will not be used within 150 feet of pillar workings or longwall faces when production is occurring.

(l) Prior to surveying, the area will be examined according to 30 CFR 75.360. If the area has not been examined, a supplemental examination according to 30 CFR 75.361 will be performed before any non-certified person enters the area.

(m) A qualified person, as defined in 30 CFR 75.151, will continuously monitor for methane immediately before and during the use of nonpermissible electronic surveying equipment within 150 feet of pillar workings and longwall faces. If there are two people in the surveying crew, both persons will continuously monitor for methane. The other person will either be a qualified person, as defined in 30 CFR 75.151, or be in the process of being trained to be a qualified person but has yet to make such tests for a period of 6 months, as required in 30 CFR 75.150. Upon completion of the 6-month training period, the second person on the surveying crew must become qualified, as defined in 30 CFR 75.151, in order to continue on the surveying crew. If the surveying crew consists of one person, that person will monitor for methane with two separate devices.

(n) Batteries contained in the nonpermissible electronic surveying equipment will be changed out or charged in fresh air more than 150 feet from pillar workings or longwall faces. Replacement batteries will be carried only in the compartment provided for a

spare battery in the nonpermissible electronic surveying equipment carrying case. Before each shift of surveying, all batteries for the nonpermissible electronic surveying equipment will be charged sufficiently so that they are not expected to be replaced on that shift.

(o) When using nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces, the surveyor will confirm by measurement or by inquiry of the person in charge of the section, that the air quantity on the section, on that shift, within 150 feet of pillar workings or longwall faces is at least the minimum quantity that is required by the mine's ventilation plan.

(p) Personnel engaged in the use of nonpermissible electronic surveying equipment will be properly trained to recognize the hazards and limitations associated with the use of such equipment in areas where methane could be present.

(q) All members of the surveying crew will receive specific training on the terms and conditions of the petition before using nonpermissible electronic surveying equipment within 150 feet of pillar workings or longwall faces. A record of the training will be kept with the other training records.

(r) If the petition is granted, the operator will submit within 60 days after the petition is final, proposed revisions for its approved 30 CFR part 48 training plans to the District Manager. These revisions will specify initial and refresher training regarding the terms and conditions of the petition. When training is conducted on the terms and conditions in the petition, an MSHA Certificate of Training (Form 5000-23) will be completed and will indicate that it was surveyor training.

(s) The operator will replace or retire from service any electronic surveying instrument that was acquired prior to December 31, 2004 within 1 year of the petition becoming final. Within 3 years of the date that the petition becomes final, the operator will replace or retire from service any theodolite that was acquired more than 5 years prior to the date that the petition becomes final or any total station or other electronic surveying equipment identified in this petition and acquired more than 10 years prior to the date that the petition becomes final. After 5 years, the operator will maintain a cycle of purchasing new electronic surveying equipment whereby theodolites will be no older than 5 years from the date of manufacture and total stations and other electronic surveying equipment will be no older than 10 years from the date of manufacture.

(t) The operator will ensure that all surveying contractors hired by the operator are using nonpermissible electronic surveying equipment in accordance with the terms and conditions of this petition. The conditions of use in the petition will apply to all nonpermissible electronic surveying equipment used within 150 feet of pillar workings or longwall faces, regardless of whether the equipment is used by the operator or by an independent contractor.

(u) The petitioner states that it may use nonpermissible electronic surveying equipment when production is occurring, subject to the following conditions:

- On a mechanized mining unit (MMU) where production is occurring, nonpermissible electronic surveying equipment will not be used downwind of the discharge point of any face ventilation controls, such as tubing (including controls such as “baloney skins”) or curtains.
- Production may continue while nonpermissible electronic surveying equipment is used, if such equipment is used in a separate split of air from where production is occurring.
- Nonpermissible electronic surveying equipment will not be used in a split of air ventilating an MMU if any ventilation controls will be disrupted during such surveying. Disruption of ventilation controls means any change to the mine's ventilation system that causes the ventilation system not to function in accordance with the mine's approved ventilation plan.
- If, while surveying, a surveyor must disrupt ventilation, the surveyor will cease surveying and communicate to the section foreman that ventilation must be disrupted. Production will stop while ventilation is disrupted. Ventilation controls will be reestablished immediately after the disruption is no longer necessary. Production will only resume after all ventilation controls are reestablished and are in compliance with approved ventilation or other plans, and other applicable laws, standards, or regulations.
- Any disruption in ventilation will be recorded in the logbook required by the petition. The logbook will include a description of the nature of the disruption, the location of the disruption, the date and time of the disruption and the date and time the surveyor communicated the disruption to the section foreman, the date and time production ceased, the date and time ventilation was reestablished, and the date and time production resumed.

—All surveyors, section foremen, section crew members, and other personnel who will be involved with or affected by surveying operations will receive training in accordance with 30 CFR 48.7 on the requirements of the petition within 60 days of the date the petition becomes final. The training will be completed before any nonpermissible electronic surveying equipment can be used while production is occurring. The operator will keep a record of the training and provide the record to MSHA on request.

—The operator will provide annual retraining to all personnel who will be involved with or affected by surveying operations in accordance with 30 CFR 48.8. The operator will train new miners on the requirements of the petition in accordance with 30 CFR 48.5, and will train experienced miners, as defined in 30 CFR 48.6, on the requirements of the petition in accordance with 30 CFR 48.6. The operator will keep a record of the training and provide the record to MSHA on request.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

Sheila McConnell,

Director, Office of Standards, Regulations, and Variances.

[FR Doc. 2019-22419 Filed 10-11-19; 8:45 am]

BILLING CODE 4520-43-P

DEPARTMENT OF LABOR

Mine Safety and Health Administration

Petitions for Modification of Application of Existing Mandatory Safety Standards

AGENCY: Mine Safety and Health Administration, Labor.

ACTION: Notice.

SUMMARY: This notice is a summary of petitions for modification submitted to the Mine Safety and Health Administration (MSHA) by the parties listed below.

DATES: All comments on the petitions must be received by MSHA's Office of Standards, Regulations, and Variances on or before November 14, 2019.

ADDRESSES: You may submit your comments, identified by “docket number” on the subject line, by any of the following methods:

1. *Electronic Mail:* zzMSHA-comments@dol.gov. Include the docket